

# Audi Q5



## 40 TDI quattro S tronic 150 kW MHEV

### Engine / electrics

Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1968 / 81.0 x 95.5 / 15.5
Max. power output in kW (PS) / at rpm	150 (204) / 3800 - 4200
Max. torque in Nm ( <i>lb-ft</i> ) / at rpm	400 (295.0) / 1750 - 3250
Mixture preparation	Common rail fuel injection system, intercooler
Exhaust emission control	Oxidizing catalytic converter, diesel particulate filter, exhaust gas recirculation, SCR catalytic converter
Emission standard	Euro 6e
Max. electrical output at 12V in kW	3.1
On-board voltage 1 in volts	12
On-board voltage 2 in volts	48

### Drivetrain / transmission

Drive type	quattro all-wheel drive with ultra technology
Type of center differential	Electronically controlled multi-plate clutch
Clutch	Hydraulically operated dual clutch (wet)
Transmission type	7-speed S tronic
Transmission ratio in 1 <sup>st</sup> /2 <sup>nd</sup> gear	3.188 / 2.190
Transmission ratio in 3 <sup>rd</sup> /4 <sup>th</sup> gear	1.517 / 1.057
Transmission ratio in 5 <sup>th</sup> /6 <sup>th</sup> gear	0.738 / 0.508
Transmission ratio in 7 <sup>th</sup> /8 <sup>th</sup> gear	0.386 / -
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.750 / 5.302 / -

### Suspension / steering / brakes

Type and design of front-axle suspension	5-link front axle
Type and design of rear-axle suspension	5-link rear axle
Tires (basic)	235 / 65 R 17
Wheels (basic)	Forged aluminum 8 J x 17
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.9
Turning circle in m ( <i>ft</i> )	11.8 (38.7)
Brake system	ESC/ABS/EBD, brake booster, hydraulic brake assist; Front: aluminum fixed calipers; Rear: floating calipers with integrated electronic parking brake
Brake disk diameter front / rear in mm ( <i>in</i> )	338 / 330 (13.3 / 13.0)

### Performance / fuel

Top speed in km/h ( <i>mph</i> )	222 (137.9)
Acceleration, 0-100 km/h (0-62.1 <i>mph</i> )	7.6
Fuel type / octane value / fuel standard	Diesel / DIN EN 590

---

### Consumption / emission\*

Fuel consumption, combined in l/100 km (US mpg)	7.1 - 6.3 (33.1 - 37.3)
CO <sub>2</sub> emissions, combined in g/km (g/mi)	187 - 165 (300.9 - 265.5)
CO <sub>2</sub> class	G - F

---

### Servicing / guarantee (Germany)

Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	17 / 25 / 27

---

### Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (lb)	1805 (3979.3) / 1880 (4144.7) / 2510 (5533.6)
Front / rear axle load limit in kg (lb)	1245 (2744.8) / 1335 (2943.2)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)	2400 (5291.1) / 2400 (5291.1) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (lb)	75 (165.3) / 100 (220.5)

---

### Capacities

Cooling system capacity (incl. heating) in l (US gal)	12.3 (3.2)
Engine oil capacity, including filter (change volume) in l (US qt)	5.5 (5.8)
Fuel tank capacity / optional in l (US gal)	65 (17.2) / 70 (18.5)
AdBlue fuel tank capacity / optional in l (US gal)	12 (3.2) / 24 (6.3)

---

### Dimensions\*\* / body

Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 5 / 5
Drag coefficient C <sub>d</sub> / frontal area A in m <sup>2</sup> (sq ft)	0.31 / 2.64 (28.4)
Vehicle height from - to in mm (ft)	1614 (5.3) - 1668 (5.5)
Vehicle length from - to in mm (ft)	4682 (15.4) - 4682 (15.4)
Vehicle width, without mirrors, from - to in mm (ft)	1893 (6.2) - 1893 (6.2)
Vehicle width, including mirrors, in mm (ft)	2140 (7.0)
Wheelbase (full load) from - to // track width front/rear in mm (ft)	2824 (9.3) - 2832 (9.3) // 1616 (5.3) / 1609 (5.3)
Overhang angle, front / rear in degrees	21.1 / 25.2
Height of loading edge from - to in mm (ft)	727 - 763 (2.4 - 2.5)
Luggage compartment behind the 2 <sup>nd</sup> seat row in l (cu ft)	515 (18.2)
Largest luggage capacity behind the 1 <sup>st</sup> seat row in l (cu ft)	1515 (53.5)

\*Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO<sub>2</sub> emissions and performance figures.

\*\*Value range taking into account different chassis and equipment lines in relation to the basic model.