

Audi e-tron GT



quattro 350 kW

Drivetrain / transmission / battery

Drive type	All-wheel drive
Type of rear axle differential	Standard
Transmission type	2-speed / automatic
Peak electrical output in kW	350
Peak electrical output boost in kW	390
Continuous electrical output in kW	140
Battery type / number of cells	Lithium-Ion
Gross / net battery capacity in kWh	93.4 / 83.7
Max. charging capacity AC / DC in kW	11.0 / 270
Max. charging capacity AC / DC optional in kW	22.0 / -
Charging time DC 5-80% in min	22.5
Min. charging time AC 0-100% in h	9.5
Min. charging time AC 0-100% optional in h	5
On-board voltage 1 in volts	12
On-board voltage 2 in volts	800

Suspension / steering / brakes

Type and design of front-axle suspension	Double-wishbone suspension
Type and design of rear-axle suspension	Multi-link suspension
Tires (basic)	225/55 R 19 275/45 R 19
Wheels (basic)	Alloy 8 J x 19" 10 J x 19"
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.4
Turning circle in m (ft)	11.6 (38.1)
Brake system	Dual-circuit brake system with black/white split for front/rear axles; ESC/ABS/EBD; brake booster, hydraulic brake assist

Performance / range / acoustics

Top speed in km/h (mph)	245 (152.2) (limited)
electrical acceleration, 0-100 km/h (62.1 mph) in s	4.5
Electrical acceleration boost, 0-100 km/h (62.1 mph) in s	4.1
Electrical range, combined according to WLTP in km (mi)	501 - 458 (311.3 - 284.6)
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	- / 69

Consumption / emission*

Electric power consumption, combined according to WLTP in kWh/100 km (62.1 mi)	21.6 - 19.6
CO2 emissions, combined in g/km (g/mi)	0

Servicing / guarantee (Germany)

Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	19 / 29 / 27

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (lb)	2276 / 2351 / 2840 (5017.7 / 5183.1 / 6261.1)
Front / rear axle load limit in kg (lb)	1395 / - (3075.4 / -)
Roof load limit / permissible nose weight in kg (lb)	75 / - (165.3 / -)

Dimensions / body

Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 4/ 5
Drag coefficient C _d / frontal area A in m ² (sq ft)	0.24 / 2.35 (25.3)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (ft)	4989 / 1964 / 1413 / 1396 (16.4 / 6.4 / 4.6 / 4.6)
Vehicle width, including mirrors, in mm (in)	2158 (7.1)
Wheelbase // track width front / rear in mm (ft)	2900 // 1710 / 1694 (9.5 // 5.6 / 5.6)
Overhang angle of steel springs, front / rear in degrees	13.0 / 16.4
Overhang angle of air springs, front / rear in degrees	16.00 / 12.00
Height of loading edge in mm (ft)	681 (2.2)
Closed luggage compartment - behind the 2nd seat row in l (cu ft)	405 (14.3)

*Figures depend on the equipment selected.