

Audi Q4

45 e-tron 210 kW



Drivetrain / transmission / battery

| | |
|--|-------------------|
| Drive type | Rear-wheel drive |
| Number of electric motors front axle / rear axle | 0 / 1 |
| Peak electrical output in kW | 210 |
| Continuous electrical output in kW | 87 |
| Electrical torque output front / rear in Nm (<i>lb-ft</i>) | - / 545 (402.0) |
| Battery type / number of cells | Lithium-Ion / 192 |
| Gross / net battery capacity in kWh | 82 / 77 |
| Max. charging capacity AC / DC in kW | 11 / 135 |
| Charging time AC 0-100%, 3ph 16A@230V in min | 480 |
| On-board voltage 1 in volts | 12 |
| Voltage level of the HV battery in volts | 400 |

Suspension / steering / brakes

| | |
|--|--|
| Type and design of front-axle suspension | McPherson struts, front |
| Type and design of rear-axle suspension | 4-link rear axle |
| Tires (basic) | 235 / 55 R 19 255 / 50 R 19 |
| Wheels (basic) | Steel 8 J x 19 |
| Steering | Electromechanical steering with speed-dependent power assistance |
| Steering ratio | 15.6 |
| Turning circle in m (<i>ft</i>) | 10.2 (33.5) |
| Brake system | Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: floating caliper |

Performance / range

| | |
|---|---------------------------|
| Top speed in km/h (<i>mph</i>) | 180 (111.8) (governed) |
| electrical acceleration, 0-100 km/h (62.1 <i>mph</i>) in s | 6.7 |
| Electrical range, combined in km (<i>mi</i>) | 455 - 544 (282.7 - 338.0) |

Consumption / emission*

| | |
|--|-------------|
| Electric power consumption, combined in kWh/100 km (62.1 <i>mi</i>) | 19.2 - 16.2 |
| CO ₂ emissions, combined in g/km (<i>g/mi</i>) | 0 |
| CO ₂ class | A |

Servicing / guarantee (Germany)

| | |
|--|------------------|
| Service interval | 2 years |
| Vehicle / paint / rust perforation guarantee | 2 / 3 / 12 years |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 17 / 23 / 21 |

Weights / loads

| | |
|--|--|
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 2070 / 2145 / 2660 (4563.6 / 4728.9 / 5864.3) |
| Front / rear axle load limit in kg (<i>lb</i>) | 1200 / 1530 (2645.5 / 3373.1) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 1200 / 1000 // 750 (2645.5 / 2204.6 // 1653.5) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 75 / 75 (165.3 / 165.3) |

Dimensions / body**

| | |
|---|---|
| Body type / number of doors / number of seats | Unitary steel / 5 / 5 |
| Drag coefficient C_d / frontal area A in m ² (<i>sq ft</i>) | 0.29 / 2.55 (27.4) |
| Vehicle height from - to in mm (<i>ft</i>) | 1599 - 1639 (5.2 - 5.4) |
| Vehicle length from - to in mm (<i>ft</i>) | 4588 - 4591 (15.1 - 15.1) |
| Vehicle width, without mirrors, in mm (<i>ft</i>) | 1865 - 1865 (6.1 - 6.1) |
| Vehicle width, including mirrors, in mm (<i>ft</i>) | 2108 (6.9) |
| Wheelbase (full load) from - to // track width front/rear in mm (<i>ft</i>) | 2771 - 2773 (9.1 - 9.1) // 1587(5.2) / 1565 (5.1) |
| Overhang angle, front / rear in degrees | 17.7 / 23.3 |
| Height of loading edge in mm (<i>ft</i>) | 783 (2.6) |
| Luggage compartment behind the 2 nd seat row in l (<i>cu ft</i>) | 520 (18.4) |

*Information on fuel/power consumption and CO₂ emissions in ranges depending on the chosen equipment level of the car.

**Value range taking into account different chassis (steel spring and air spring) and equipment lines in relation to the basic model.