

Audi Q4 Sportback



35 e-tron 125 kW

Drivetrain / transmission / battery

Drive type	Rear-wheel drive
Number of electric motors front axle / rear axle	0 / 1
Electrical output in kW	125
Electrical torque output front / rear in Nm (<i>lb-ft</i>)	- / 310 (228.6)
Battery type / number of cells	Lithium-Ion / 96
Gross / net battery capacity in kWh	55 / 52
Max. charging capacity AC / DC in kW	11 / 145
Min. charging time DC 10-80% in min	25
Charging time AC 0-100%, 3ph 16A@230V in min	330
On-board voltage 1 in volts	12
Voltage level of the HV battery in volts	400

Suspension / steering / brakes

Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	4-link rear axle
Tires (basic)	235 / 55 R 19 255 / 50 R 19
Wheels (basic)	Steel 8 J x 19
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.6
Turning circle in m (<i>ft</i>)	10.2 (33.5)
Brake system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: floating caliper

Performance / range

Top speed in km/h (<i>mph</i>)	160 (99.4) (governed)
electrical acceleration, 0-100 km/h (62.1 <i>mph</i>) in s	9
Electrical range, combined in km (<i>mi</i>)	325 - 365 (201.9 - 226.8)

Consumption / emission*

Electric power consumption, combined in kWh/100 km (62.1 <i>mi</i>)	18.7 - 16.4
CO ₂ emissions, combined in g/km (<i>g/mi</i>)	0
CO ₂ class	A

Servicing / guarantee (Germany)

Service interval	2 years
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 20 / 20

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1915 / 1990 / 2500 (4221.9 / 4387.2 / 5511.6)
Front / rear axle load limit in kg (<i>lb</i>)	1150 / 1420 (2535.3 / 3130.6)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1200 / 1000 // 750 (2645.5 / 2204.6 // 1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	75 / 75 (165.3 / 165.3)

Dimensions / body**

Body type / number of doors / number of seats	Unitary steel / 5 / 5
Drag coefficient C_d / frontal area A in m ² (<i>sq ft</i>)	0.28 / 2.55 (27.4)
Vehicle height from - to in mm (<i>ft</i>)	1581 - 1622 (5.2 - 5.3)
Vehicle length from - to in mm (<i>ft</i>)	4588 - 4591 (15.1 - 15.1)
Vehicle width, without mirrors, from - to in mm (<i>ft</i>)	1865 - 1865 (6.1 - 6.1)
Vehicle width, including mirrors, in mm (<i>ft</i>)	2108 (6.9)
Wheelbase (full load) from - to // track width front/rear in mm (<i>ft</i>)	2771 - 2773 (9.1 - 9.1) // 1587(5.2) / 1563 (5.1)
Overhang angle, front / rear in degrees	17.7 / 23.3
Height of loading edge from - to in mm (<i>ft</i>)	768 - 784 (2.5 - 2.6)
Luggage compartment behind the 2 nd seat row in l (<i>cu ft</i>)	535 (18.9)

*Information on fuel/power consumption and CO₂ emissions in ranges depending on the chosen equipment level of the car.

**Value range taking into account different chassis and equipment lines in relation to the basic model.