# Audi Q4 Sportback

## 40 e-tron 150 kW

### Drivetrain / transmission / battery

| | |
|---|---|
| Drive type | Rear-wheel drive |
| Number of electric motors front axle / rear axle | 0 / 1 |
| Max. electrical output in kW | 150 |
| Electrical torque output front / rear in Nm *(lb-ft)* | - / 310 *(228.6)* |
| Battery type / number of cells | Lithium-Ion / 108 |
| Gross / net battery capacity in kWh | 63 / 59 |
| Max. charging capacity AC / DC in kW | 11 / 165 |
| Charging time DC 10-80% in min | 24 |
| Charging time AC 0-100%, 3ph 16A@230V in min | 390 |
| On-board voltage 1 in volts | 12 |
| Voltage level of the HV battery in volts | 400 |

### Suspension / steering / brakes

| | |
|---|---|
| Type and design of front-axle suspension | McPherson struts, front |
| Type and design of rear-axle suspension | 4-link rear axle |
| Tires (basic) | 235 / 55 R 19 \| 255 / 50 R 19 |
| Wheels (basic) | Stahl 8 J x 19 |
| Steering | Electromechanical steering with speed-dependent power assistance |
| Steering ratio | 15.6 |
| Turning circle in m *(ft)* | 10.2 *(33.5)* |
| Brake system | Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: floating caliper |

### Performance / range

| | |
|---|---|
| Top speed in km/h *(mph)* | 160 *(99.4)* (governed) |
| electrical acceleration, 0-100 km/h *(62.1 mph)* in s | 8.1 |
| Electrical range, combined in km *(mi)* | 379 - 423 *(235.5 - 262.8)* |

### Consumption / emission*

| | |
|---|---|
| Electric power consumption, combined in kWh/100 km *(62.1 mi)* | 18.0 - 16.0 |
| $CO_2$ emissions, combined in g/km *(g/mi)* | 0 |
| $CO_2$ class | A |

### Servicing / guarantee (Germany)

| | |
|---|---|
| Service interval | 2 years |
| Vehicle / paint / rust perforation guarantee | 2 / 3 / 12 years |
| Insurance classification in Germany:<br>third party / fully comprehensive / part-comprehensive | 16 / 20 / 20 |

## Weights / loads

| | |
|---|---|
| Unladen weight without driver / with driver / gross weight limit in kg *(lb)* | 1960 / 2035 / 2540 *(4321.1 / 4486.4 / 5599.7)* |
| Front / rear axle load limit in kg *(lb)* | 1175 / 1435 *(2590.4 / 3163.6)* |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg *(lb)* | 1200 / 1000 // 750 *(2645.5 / 2204.6 // 1653.5)* |
| Roof load limit / permissible nose weight in kg *(lb)* | 75 / 75 *(165.3 / 165.3)* |

## Dimensions** / body

| | |
|---|---|
| Body type / number of doors / number of seats | Unitary steel / 5/ 5 |
| Drag coefficient $C_d$ / frontal area A in $m^2$ *(sq ft)* | 0.28 / 2.55 *(27.4)* |
| Vehicle height from - to in mm *(ft)* | 1581 - 1622 *(5.2 - 5.3)* |
| Vehicle length from - to in mm *(ft)* | 4588 - 4591 *(15.1 - 15.1)* |
| Vehicle width, without mirrors, from - to in mm *(ft)* | 1865 - 1865 *(6.1 - 6.1)* |
| Vehicle width, including mirrors, in mm *(ft)* | 2108 *(6.9)* |
| Wheelbase (full load) from - to // track width front/rear in mm *(ft)* | 2770 - 2772 *(9.1 - 9.1)* // 1587 *(5.2)* / 1563 *(5.1)* |
| Overhang angle, front / rear in degrees | 17.7 / 23.4 |
| Height of loading edge from - to in mm *(ft)* | 768 - 784 *(2.5 - 2.6)* |
| Luggage compartment behind the 2nd seat row in l *(cu ft)* | 535 *(18.9)* |
| Largest luggage capacity behind the 1st seat row in l *(cu ft)* | 1460 *(51.6)* |

***Information on fuel/power consumption and $CO_2$ emissions in ranges depending on the chosen equipment level of the car.**
****Value range taking into account different chassis and equipment lines in relation to the basic model.**