

# Audi Q4 Sportback



## 45 e-tron 210 kW

---

### Drivetrain / transmission / battery

Drive type	Rear-wheel drive
Number of electric motors front axle / rear axle	0 / 1
Electrical output in kW	210
Electrical torque output front / rear in Nm ( <i>lb-ft</i> )	- / 545 (402.0)
Battery type / number of cells	Lithium-Ion / 288
Gross / net battery capacity in kWh	82 / 77
Max. charging capacity AC / DC in kW	11 / 175
Min. charging time DC 10-80% in min	28
Charging time AC 0-100%, 3ph 16A@230V in min	480
On-board voltage 1 in volts	12
Voltage level of the HV battery in volts	400

---

### Suspension / steering / brakes

Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	4-link rear axle
Tires (basic)	235 / 55 R 19   255 / 50 R 19
Wheels (basic)	Steel 8 J x 19
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.6
Turning circle in m ( <i>ft</i> )	10.2 (33.5)
Brake system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: floating caliper

---

### Performance / range

Top speed in km/h ( <i>mph</i> )	180 (111.8) (governed)
electrical acceleration, 0-100 km/h (62.1 <i>mph</i> ) in s	6.7
Electrical range, combined in km ( <i>mi</i> )	516 - 579 (320.6 - 359.8)

---

### Consumption / emission\*

Electric power consumption, combined in kWh/100 km (62.1 <i>mi</i> )	17.6 - 15.5
CO <sub>2</sub> emissions, combined in g/km ( <i>g/mi</i> )	0
CO <sub>2</sub> class	A

---

### Servicing / guarantee (Germany)

Service interval	2 years
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 23 / 20

---

**Weights / loads**

Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	2070 / 2145 / 2660 (4563.6 / 4728.9 / 5864.3)
Front / rear axle load limit in kg ( <i>lb</i> )	1200 / 1530 (2645.5 / 3373.1)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1200 / 1000 // 750 (2645.5 / 2204.6 // 1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 / 75 (165.3 / 165.3)

---

**Dimensions\*\* / body**

Body type / number of doors / number of seats	Unitary steel / 5 / 5
Drag coefficient $C_d$ / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.28 / 2.55 (27.4)
Vehicle height from - to in mm ( <i>ft</i> )	1581 - 1622 (5.2 - 5.3)
Vehicle length from - to in mm ( <i>ft</i> )	4588 - 4591 (15.1 - 15.1)
Vehicle width, without mirrors, from - to in mm ( <i>ft</i> )	1865 - 1865 (6.1 - 6.1)
Vehicle width, including mirrors, in mm ( <i>ft</i> )	2108 (6.9)
Wheelbase (full load) from - to // track width front/rear in mm ( <i>ft</i> )	2771 - 2773 (9.1 - 9.1) // 1587(5.2) / 1563 (5.1)
Overhang angle, front / rear in degrees	17.7 / 23.3
Height of loading edge from - to in mm ( <i>ft</i> )	768 - 784 (2.5 - 2.6)
Luggage compartment behind the 2 <sup>nd</sup> seat row in l ( <i>cu ft</i> )	535 (18.9)

\*Information on fuel/power consumption and CO<sub>2</sub> emissions in ranges depending on the chosen equipment level of the car.

\*\*Value range taking into account different chassis and equipment lines in relation to the basic model.