

# Audi Q4 Sportback



## 45 e-tron quattro 210 kW

### Drivetrain / transmission / battery

Drive type	All-wheel drive
Number of electric motors front axle / rear axle	1 / 1
Peak electrical output in kW	210
Electrical torque output front / rear in Nm ( <i>lb-ft</i> )	134 / 545 ( <i>98.8 / 402.0</i> )
Battery type / number of cells	Lithium-Ion / 288
Gross / net battery capacity in kWh	82 / 77
Max. charging capacity AC / DC in kW	11 / 175
Charging time AC 0-100%, 3ph 16A@230V in min	480
On-board voltage 1 in volts	12
Voltage level of the HV battery in volts	400

### Suspension / steering / brakes

Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	4-link rear axle
Tires (basic)	235 / 55 R 19   255 / 50 R 19
Wheels (basic)	Steel 8 J x 19
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.6
Turning circle in m ( <i>ft</i> )	11.5 ( <i>37.7</i> )
Brake system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: floating caliper

### Performance / range

Top speed in km/h ( <i>mph</i> )	180 ( <i>111.8</i> ) (governed)
electrical acceleration, 0-100 km/h ( <i>62.1 mph</i> ) in s	6.6
Electrical range, combined in km ( <i>mi</i> )	465 - 539 ( <i>288.9 - 334.9</i> )

### Consumption / emission\*

Electric power consumption, combined in kWh/100 km ( <i>62.1 mi</i> )	18.9 - 16.2
CO <sub>2</sub> emissions, combined in g/km ( <i>g/mi</i> )	0
CO <sub>2</sub> class	A

### Servicing / guarantee (Germany)

Service interval	2 years
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	17 / 23 / 21

---

**Weights / loads**

Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	2160 / 2235 / 2750 (4762.0 / 4927.3 / 6062.7)
Front / rear axle load limit in kg ( <i>lb</i> )	1285 / 1535 (2832.9 / 3384.1)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1400 / 1200 // 750 (3086.5 / 2645.5 // 1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 / 75 (165.3 / 165.3)

---

**Dimensions\*\* / body**

Body type / number of doors / number of seats	Unitary steel / 5 / 5
Drag coefficient $C_d$ / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.27 / 2.55 (27.4)
Vehicle height from - to in mm ( <i>ft</i> )	1581 - 1622 (5.2 - 5.3)
Vehicle length from - to in mm ( <i>ft</i> )	4588 - 4591 (15.1 - 15.1)
Vehicle width, without mirrors, in mm ( <i>ft</i> )	1865 - 1865 (6.1 - 6.1)
Vehicle width, including mirrors, in mm ( <i>ft</i> )	2108 (6.9)
Wheelbase (full load) from - to // track width front/rear in mm ( <i>ft</i> )	2771 - 2773 (9.1 - 9.1) // 1587(5.2) / 1565 (5.1)
Overhang angle, front / rear in degrees	17.7 / 23.3
Height of loading edge in mm ( <i>ft</i> )	783 (2.6)
Luggage compartment behind the 2 <sup>nd</sup> seat row in l ( <i>cu ft</i> )	535 (18.9)

\*Information on fuel/power consumption and CO<sub>2</sub> emissions in ranges depending on the chosen equipment level of the car.

\*\*Value range taking into account different chassis (steel spring and air spring) and equipment lines in relation to the basic model.