

# Audi SQ8 Sportback



e-tron 370 kW

## Drivetrain / transmission / battery

Drive type	All-wheel drive
Number of electric motors front axle / rear axle	1 / 2
Transmission type	2-stage ratio planetary gearbox with a single gear
Peak electrical output in kW	370
Continuous electrical output in kW	140
Electrical torque output front / rear in Nm ( <i>lb-ft</i> )	309 (227.9) / 355 (261.8)
Battery type / number of cells	Lithium-Ion / 432
Gross / net battery capacity in kWh	114 / 106
Max. charging capacity AC / DC in kW	11 / 170
Max. charging capacity AC / DC optional in kW	22 / -
Charging time AC 0-100%, 3ph 16A@230V in min	690
On-board voltage 1 in volts	12

## Suspension / steering / brakes

Type and design of front-axle suspension	5-link front axle
Type and design of rear-axle suspension	5-link rear axle
Tires (basic)	285 / 45 R 20
Wheels (basic)	Cast aluminum flow forming 10 J x 20
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	14.6
Turning circle in m ( <i>ft</i> )	12.2 (40.0)
Brake system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; front: aluminum fixed caliper; rear: floating caliper with integrated electronic parking brake
Brake disk diameter front / rear in mm ( <i>in</i> )	400 (15.7) / 350 (13.8)

## Performance / range

Top speed in km/h ( <i>mph</i> )	210 (130.5) (governed)
electrical acceleration, 0-100 km/h (62.1 <i>mph</i> ) in s	5.1
Electrical acceleration boost, 0-100 km/h (62.1 <i>mph</i> ) in s	4.5
Electrical range, combined in km ( <i>mi</i> )	428 - 471 (265.9 - 292.7)

## Consumption / emission\*

Electric power consumption, combined in kWh/100 km (62.1 <i>mi</i> )	28.2 - 25.3
CO <sub>2</sub> emissions, combined in g/km ( <i>g/mi</i> )	0
CO <sub>2</sub> class	A

---

**Servicing / guarantee (Germany)**

---

Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	21 / 26 / 24

---

**Weights / loads**

---

Unladen weight without driver / with driver / gross weight limit in kg (lb)	2650 (5842.2) / 2725 (6007.6) / 3290 (7253.2)
Front / rear axle load limit in kg (lb)	1580 (3483.3) / 1810 (3990.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)	1800 (3968.3) / 1800 (3968.3) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (lb)	75 (165.3) / 80 (176.4)

---

**Dimensions\*\* / body**

---

Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 5 / 5
Drag coefficient C <sub>d</sub> / frontal area A in m <sup>2</sup> (sq ft)	0.27 / 2.71 (29.2)
Vehicle height from - to in mm (ft)	1617 (5.3)
Vehicle length from - to in mm (ft)	4915 (16.1)
Vehicle width, without mirrors, in mm (ft)	1976 (6.5)
Vehicle width, including mirrors, in mm (ft)	2189 (7.2)
Wheelbase (full load) from - to // track width front/rear in mm (ft)	2928 (9.6) // 1683 (5.5) / 1683 (5.5)
Height of loading edge in mm (ft)	802 (2.6)
Luggage compartment behind the 2 <sup>nd</sup> seat row in l (cu ft)	528 (18.6)
Largest luggage capacity behind the 1 <sup>st</sup> seat row in l (cu ft)	1567 (55.3)

\*Information on fuel/power consumption and CO<sub>2</sub> emissions in ranges depending on the chosen equipment level of the car.

\*\*Value range taking into account different chassis and equipment lines in relation to the basic model.