Audi R8 Coupé V10 GT



RWD 456 kW

| Engine / electrics | |
|---|--|
| Engine type | V10 engine |
| Valve gear / number of valves per cylinder | Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valv play compensation / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 5204 / 84.5 x 92.8 / 12.7 |
| Max. power output in kW (PS) / at rpm | 456 (620) / 8000 |
| Max. torque in Nm (lb-ft) / at rpm | 565 <i>(416.7)</i> / 6400 - 7000 |
| Mixture preparation | Direct injection, lambda control, knock control |
| Exhaust emission control | Close coupled catalytic converter, oxygen sensor |
| Emission standard | Euro 6d-ISC-FCM |
| Max. electrical output at 12V in kW | 2.2 |
| On-board voltage 1 in volts | 12 |
| Drivetrain / transmission | _ |
| Drive type | Rear-wheel drive |
| Type of rear axle differential | Mechanical differential lock |
| Clutch | Hydraulically operated dual clutch (wet) |
| Transmission type | 7-speed S tronic |
| Transmission ratio in 1st/2nd gear | 3.133 / 2.588 |
| Transmission ratio in 3 rd /4 th gear | 1.958 / 1.244 |
| Transmission ratio in 5 th /6 th gear | 0.979 / 0.976 |
| Transmission ratio in 7 th /8 th gear | 0.841 / - |
| Reverse gear ratio / final drive ratio 1-2 / 2-3 | 2.647 / 4.893 / 3.938 |
| Suspension / steering / brakes | _ |
| Type and design of front-axle suspension | Double-wishbone suspension |
| Type and design of rear-axle suspension | Double-wishbone suspension |
| Tires (basic) | 245/30 305/30 R 20 |
| Wheels (basic) | Forged aluminum 8.5] 11 x 20 |
| Steering | Electromechanical steering with speed-dependent power assistance |
| Turning circle in m (ft) | 11.2 (36.7) |
| Brake system | Diagonal dual-circuit brake system with ESC/ABS/EBD, brake booster, hydraulic brake assist; Front and rear aluminum fixed calipers |
| Brake disk diameter front / rear in mm (in) | 380 (15.0) / 356 (14.0) |
| Performance / fuel / acoustics | _ |
| Top speed in km/h (mph) | 320 (198.8) |

Gasoline / 95 / DIN EN 228

91.0 / 72

Acceleration, 0-100 km/h (0-62.1 mph)
Fuel type / octane value / fuel standard

Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (\emph{A})

| Consumption / emission* | |
|---|--|
| Fuel consumption, combined according to WLTP in I/100 km (US mpg) | 15.0 - 14.9 <i>(15.7 - 15.8)</i> |
| CO ₂ emissions, combined according to WLTP in g/km (g/mi) | 341 - 339 <i>(548.8 - 545.6)</i> |
| Servicing / guarantee (Germany) | |
| Service interval | 30,000 km (18,641.1 mi) / 2 years, whichever comes first |
| Vehicle / paint / rust perforation guarantee | 2 / 3 / 12 years |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 21/34/31 |
| Weights / loads | |
| Unladen weight without driver / with driver / gross weight limit in kg (lb) | 1570 (3461.3) / 1645 (3626.6) / 1875 (4133.7) |
| Front / rear axle load limit in kg (lb) | 875 (1929.0) / 1130 (2491.2) |
| Capacities | |
| Cooling system capacity (incl. heating) in l (US gal) | 24.7 (6.5) |
| Engine oil capacity, including filter (change volume) in l (US qt) | 8.3 (8.8) |
| Fuel tank capacity / optional in l (US gal) | 73 (19.3) / - |
| Dimensions / body | |
| Body type / number of doors / number of seats | Audi Space Frame (ASF) / 2 / 2 |
| Drag coefficient C _d / frontal area A in m ² (sq ft) | 0.42 / 2.01 (21.6) |
| Standard dimensions (length / width excluding mirrors / height with steel springs / air springs) in mm (ft) | 4496 (14.8) / 1964 (3.2) / 1225 (4.0) / - |
| Vehicle width, including mirrors, in mm (in) | 2037 (6.7) |
| Wheelbase // track width front/rear in mm (ft) | 2650 (8.7) // 1645 (5.4) / 1599 (5.2) |

^{*}Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO₂ emissions and performance figures.