

# Audi Q6



## SUV e-tron quattro 285 kW

### Drivetrain / transmission / battery

Drive type	All-wheel drive
Number of electric motors front axle / rear axle	1 / 1
Electrical output in kW	285
Electrical torque output front / rear in Nm ( <i>lb-ft</i> )	275 / 580 (202.8 / 427.8)
Battery type / number of cells	Lithium-Ion / 180
Gross / net battery capacity in kWh	100 / 94.9
Max. charging capacity AC / DC in kW	11 / 270
Charging time AC 0-100%, 3ph 16A@230V in min	600
On-board voltage 1 in volts	12
Voltage level of the HV battery in volts	800

### Suspension / steering / brakes

Type and design of front-axle suspension	5-link front axle
Type and design of rear-axle suspension	5-link rear axle
Tires (basic)	235 / 65 R 18   255 / 60 R 18
Wheels (basic)	Cast aluminum - 8 J x 18   Cast aluminum 9 J x 18
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	16.3
Turning circle in m ( <i>ft</i> )	12.1 (39.7)
Brake system	ESC/ABS/EBD/ brake unit, hydraulic brake assist; front: aluminum fixed caliper; rear: floating caliper with integrated electronic parking brake
Brake disk diameter front / rear in mm ( <i>in</i> )	375 (14.8) / 350 (13.8)

### Performance / range

Top speed in km/h ( <i>mph</i> )	210 (130.5) (governed)
electrical acceleration, 0-100 km/h (62.1 <i>mph</i> ) in s	5.9
Electrical range, combined in km ( <i>mi</i> )	540 - 625 (335.5 - 388.4)

### Consumption / emission\*

Electric power consumption, combined in kWh/100 km (62.1 <i>mi</i> )	19.6 - 17.0
CO <sub>2</sub> emissions, combined in g/km ( <i>g/mi</i> )	0
CO <sub>2</sub> class	A

### Servicing / guarantee (Germany)

Service interval	2 years
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	21 / 27 / 24

---

**Weights / loads**

Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	2325 / 2400 / 2940 (5125.7 / 5291.1 / 6481.6)
Front / rear axle load limit in kg ( <i>lb</i> )	1380 / 1650 (3042.4 / 3637.6)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	2400 / 2400 // 750 (5291.1 / 5291.1 // 1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 / 100 (165.3 / 220.5)

---

**Dimensions\*\* / body**

Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 5/ 5
Drag coefficient $C_d$ / frontal area A in m <sup>2</sup> ( <i>sq ft</i> )	0.30 / 2.73 (29.4)
Vehicle height from - to in mm ( <i>ft</i> )	1648 - 1702 (5.4 - 5.6)
Vehicle length from - to in mm ( <i>ft</i> )	4771 - 4771 (15.7 - 15.7)
Vehicle width, without mirrors, in mm ( <i>ft</i> )	1939 - 1965 (6.4 - 6.4)
Vehicle width, including mirrors, in mm ( <i>ft</i> )	2193 (7.2)
Wheelbase (full load) from - to // track width front/rear in mm ( <i>ft</i> )	2893 - 2899 (9.5 - 9.5) // 1676 / 1653 (5.5 / 5.4)
Overhang angle, front / rear in degrees	18.0 / 25.7
Height of loading edge in mm ( <i>ft</i> )	746 - 777 (2.4 - 2.5)
Luggage compartment behind the 2 <sup>nd</sup> seat row in l ( <i>cu ft</i> )	526 (18.6)
Largest luggage capacity behind the 1 <sup>st</sup> seat row in l ( <i>cu ft</i> )	1529 (54.0)

\*Information on fuel/power consumption and CO<sub>2</sub> emissions in ranges depending on the chosen equipment level of the car.

\*\*Value range taking into account different chassis and equipment lines in relation to the basic model.