

Audi Q6 SUV



e-tron quattro 285 kW

Drivetrain / transmission / battery

| | |
|--|---------------------------|
| Drive type | All-wheel drive |
| Number of electric motors front axle / rear axle | 1 / 1 |
| Max. electrical output in kW | 285 |
| Electrical torque output front / rear in Nm (<i>lb-ft</i>) | 275 / 580 (202.8 / 427.8) |
| Battery type / number of cells | Lithium-Ion / 180 |
| Gross / net battery capacity in kWh | 100 / 94.9 |
| Max. charging capacity AC / DC in kW | 11 / 270 |
| Charging time DC 10-80% in min | 21 |
| Charging time AC 0-100%, 3ph 16A@230V in min | 600 |
| On-board voltage 1 in volts | 12 |
| Voltage level of the HV battery in volts | 800 |

Suspension / steering / brakes

| | |
|--|---|
| Type and design of front-axle suspension | 5-link front axle |
| Type and design of rear-axle suspension | 5-link rear axle |
| Tires (basic) | 235 / 65 R 18 255 / 60 R 18 |
| Wheels (basic) | Cast aluminum - 8 J x 18 Cast aluminum 9 J x 18 |
| Steering | Electromechanical progressive steering with speed-dependent power assistance |
| Steering ratio | 16.3 |
| Turning circle in m (<i>ft</i>) | 12.1 (39.7) |
| Brake system | ESC/ABS/EBD/ brake unit, hydraulic brake assist; front: aluminum fixed caliper; rear: floating caliper with integrated electronic parking brake |
| Brake disk diameter front / rear in mm (<i>in</i>) | 350 (13.8) / 350 (13.8) |

Performance / range

| | |
|---|---------------------------|
| Top speed in km/h (<i>mph</i>) | 210 (130.5) (governed) |
| electrical acceleration, 0-100 km/h (62.1 <i>mph</i>) in s | 5.9 |
| Electrical range, combined in km (<i>mi</i>) | 540 - 625 (335.5 - 388.4) |

Consumption / emission*

| | |
|--|-------------|
| Electric power consumption, combined in kWh/100 km (62.1 <i>mi</i>) | 19.6 - 17.0 |
| CO ₂ emissions, combined in g/km (<i>g/mi</i>) | 0 |
| CO ₂ class | A |

Servicing / guarantee (Germany)

| | |
|--|------------------|
| Service interval | 2 years |
| Vehicle / paint / rust perforation guarantee | 2 / 3 / 12 years |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 21 / 27 / 24 |

Weights / loads

| | |
|--|--|
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 2325 / 2400 / 2940 (5125.7 / 5291.1 / 6481.6) |
| Front / rear axle load limit in kg (<i>lb</i>) | 1380 / 1650 (3042.4 / 3637.6) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 2400 / 2400 // 750 (5291.1 / 5291.1 // 1653.5) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 75 / 100 (165.3 / 220.5) |

Dimensions / body**

| | |
|--|--|
| Body type / number of doors / number of seats | Unitary steel/aluminum composite construction / 5/ 5 |
| Drag coefficient C_d / frontal area A in m ² (<i>sq ft</i>) | 0.30 / 2.73 (29.4) |
| Vehicle height from - to in mm (<i>ft</i>) | 1648 - 1702 (5.4 - 5.6) |
| Vehicle length from - to in mm (<i>ft</i>) | 4771 - 4771 (15.7 - 15.7) |
| Vehicle width, without mirrors, from - to in mm (<i>ft</i>) | 1939 - 1965 (6.4 - 6.4) |
| Vehicle width, including mirrors, in mm (<i>ft</i>) | 2193 (7.2) |
| Wheelbase (full load) from - to // track width front/rear in mm (<i>ft</i>) | 2893 - 2899 (9.5 - 9.5) // 1676 / 1653 (5.5 / 5.4) |
| Overhang angle, front / rear in degrees | 18.0 / 25.7 |
| Height of loading edge from - to in mm (<i>ft</i>) | 746 - 777 (2.4 - 2.5) |
| Luggage compartment front (frunk) in l (<i>cu ft</i>) | 64 (2.3) |
| Luggage compartment behind the 2 nd seat row in l (<i>cu ft</i>) | 526 (18.6) |
| Largest luggage capacity behind the 1 st seat row in l (<i>cu ft</i>) | 1529 (54.0) |

*Information on fuel/power consumption and CO₂ emissions in ranges depending on the chosen equipment level of the car.
**Value range taking into account different chassis and equipment lines in relation to the basic model.