

Audi RS e-tron GT



performance 550 kW

Drivetrain / transmission / battery

Drive type	All-wheel drive
Number of electric motors front axle / rear axle	1 / 1
Max. electrical output in kW	550
Max. electrical output in launch control mode in kW	680
Continuous electrical output in kW	163
Electrical torque output front / rear in Nm (lb-ft)	409 / 590 (301.7 / 435.2)
Battery type / number of cells	Lithium-Ion / 396
Gross / net battery capacity in kWh	105 / 97
Max. charging capacity AC / DC in kW	11 / 320
Max. charging capacity AC / DC optional in kW	- / 320
Charging time DC 10–80% in min	18
Charging time AC 0–100%, 3ph 16A@230V in min	660
On-board voltage 1 in volts	12
Voltage level of the HV battery in volts	800

Suspension / steering / brakes

Type and design of front-axle suspension	Double-wishbone suspension
Type and design of rear-axle suspension	Double-wishbone suspension
Tires (basic)	245 / 45 R 20 285 / 40 R 20
Wheels (basic)	Cast aluminum flow forming 9 J x 20 Cast aluminum flow forming 11 J x 20
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	15.4
Turning circle in m (ft)	11.6 (38.1)
Brake system	Dual-circuit brake system with black/white split for front/rear axles; front: aluminum fixed calipers; rear: aluminum fixed calipers
Brake disk diameter front / rear in mm (in)	410 / 365 (16.1 - 14.4)

Performance / range

Top speed in km/h (mph)	250 (155.3)
electrical acceleration, 0–100 km/h (62.1 mph) in s	2.9
Electrical acceleration in launch control mode, 0–100 km/h (62.1 mph) in s	2.5
Electrical range, combined in km (mi)	533 – 592 (331.2 – 367.9)

Consumption / emission¹

Electric power consumption, combined in kWh/100 km (62.1 mi)	20.8 – 18.7
CO ₂ emissions, combined in g/km (g/mi)	0
CO ₂ class	A

Servicing / guarantee (Germany)

Service interval	2 years
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	20 / 29 / 27

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (lb)	2320 / 2395 / 2860 (5114.7 / 5280.1 / 6305.2)
Front / rear axle load limit in kg (lb)	1395 / 1575 (3075.4 / 3472.3)
Roof load limit / permissible nose weight in kg (lb)	75 (165.3) / -

Dimensions² / body

Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 4 / 5
Drag coefficient C_d / frontal area A in m ² (sq ft)	0.26 / 2.35 (25.3)
Vehicle height from – to in mm (ft)	1369 – 1402 (4.5 – 4.6)
Vehicle length from – to in mm (ft)	4997 – 5004 (16.4 – 16.4)
Vehicle width, without mirrors, from – to in mm (ft)	1964 – 1964 (6.4 – 6.4)
Vehicle width, including mirrors, in mm (ft)	2158 (7.1)
Wheelbase (full load) from – to // track width front/rear in mm (ft)	2900 – 2901 // 1703 / 1669 (9.5 – 9.5 // 5.6 / 5.5)
Overhang angle, front / rear in degrees	10.2 / 14.4
Height of loading edge from – to in mm (ft)	666 – 684 (2.2 – 2.2)
Luggage compartment front (frunk) in l (cu ft)	77 (2.7)
Luggage compartment behind the 2 nd seat row in l (cu ft)	350 (12.4)

Program for Germany, Status: 02/02/26

¹ Information on power consumption and CO₂ emissions in range depending on the chosen equipment level of the car.
² Value ranking taking into account different chassis and equipment lines in relation to the basis model.