Audi S5 Avant



TFSI

	_
Engine / electrics	
Engine type	V6 engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve- play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	2994.6 / 84.5 x 89.0 / 12.0
Max. power output in kW (PS) / at rpm	270 (367) / 5500 - 6300
Max. torque in Nm (lb-ft) / at rpm	550 (405.7) / 1700 - 4000
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emission standard	Euro 6e
Max. electrical output at 12V in kW	3.1
On-board voltage 1 in volts	12
On-board voltage 2 in volts	48
Drivetrain / transmission	_
Drive type	quattro all-wheel drive with ultra technology
Type of center differential	Electronically controlled multi-plate clutch
Type of rear axle differential	quattro sport
Clutch	Hydraulically operated dual clutch (wet)
Transmission type	7-speed S tronic
Transmission ratio in 1st/2nd gear	3.188 / 2.190
Transmission ratio in 3 rd /4 th gear	1.517 / 1.057
Transmission ratio in 5th/6th gear	0.738 / 0.557
Transmission ratio in 7th/8th gear	0.433 / -
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.750 / 4.410 / -
Suspension / steering / brakes	_
Type and design of front-axle suspension	5-link front axle
Type and design of rear-axle suspension	5-link rear axle
Tires (basic)	245 / 40 R 19
Wheels (basic)	Cast aluminum flow forming 8,5 J x 19
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	15.2
Turning circle in m (ft)	12.1 (39.7)
Brake system	ESC/ABS/EBD, brake booster, hydraulic brake assist; Front: floating calipers; Rear: floating calipers with integrated electronic parking brake
Brake disk diameter front / rear in mm (in)	360 (14.2) / 350 (13.8)
Performance / fuel	_
Top speed in km/h (mph)	
Acceleration, 0-100 km/h (0-62.1 mph)	4.5
Fuel type / octane value / fuel standard	Gasoline / 95 / DIN EN 228

Consumption / emission*	
Fuel consumption, combined in V100 km (US mpg)	7.9 - 7.5 (29.8 - 31.4)
CO ₂ emissions, combined in g/km (g/mi)	180 - 169 <i>(289.7 - 272.0)</i>
CO ₂ class	G - F
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 28 / 27
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (lb)	1965 (<i>4332.1</i>) / 2040 (<i>4497.4</i>) / 2520 (<i>5555.6</i>)
Front / rear axle load limit in kg (lb)	1275 (2810.9) / 1340 (2954.2)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	2100 (4629.7) / 1900 (4188.8) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (lb)	90 (198.4) / 80 (176.4)
Capacities	
Cooling system capacity (incl. heating) in l (US gal)	19.0 <i>(5.0)</i>
Engine oil capacity, including filter (change volume) in l (US qt)	7.5 (7.9)
Fuel tank capacity / optional in l (US gal)	56 (14.8) / -
Dimensions** / body	
Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 5 / 5
Drag coefficient C _d / frontal area A in m² (sq ft)	0.30 / 2.30 (24.8)
Vehicle height from - to in mm (ft)	1424 - 1476 (4.7 - 4.8)
Vehicle length from - to in mm (ft)	4829 - 4835 <i>(15.8 - 15.9)</i>
Vehicle width, without mirrors, from - to in mm (ft)	1860 - 1860 <i>(6.1 - 6.1)</i>
Vehicle width, including mirrors, in mm (ft)	2099 (6.9)
Wheelbase (full load) from - to // track width front/rear in mm (ft)	2897 - 2902 (9.5 - 9.5) // 1612 (5.3) / 1597 (5.2)
Overhang angle, front / rear in degrees	13.2 / 17.6
Height of loading edge from - to in mm (ft)	640 - 672 (2.1 - 2.2)
Luggage compartment behind the 2 nd seat row in l (<i>cu ft</i>)	448 (15.8)
Largest luggage capacity behind the 1st seat row in l (cu ft)	1396 (49.3)

^{*}Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO₂ emissions and performance figures.

 $^{{\}bf **Value\ range\ taking\ into\ account\ different\ chassis\ and\ equipment\ lines\ in\ relation\ to\ the\ basic\ model.}$