# Audi A5 Sedan



TFSI S tronic 150 kW

# Engine / electrics Engine type Inline 4-cylinder engine Valve gear / number of valves per cylinder Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valveplay compensation / 2/2 inlet/exhaust valves per cylinder Displacement in cc / bore x stroke in mm / comp Max. power output in kW (PS) / at rpm Max. torque in Nm (lb-ft) / at rpm Mixture preparation Exhaust emission control

pression	1984 / 82.5 x 92.8 / 12.5
	150 (204) / 4300 - 6000
	340 (250.8) / 2000 - 4000
	Direct injection, lambda control, knock control, turbocharger, intercooler
	Catalytic converter, oxygen sensor, gasoline particulate filter
	Euro 6e
	1.6
	12

# Drivetrain / transmission

Max. electrical output at 12V in kW

On-board voltage 1 in volts

Emission standard

Drive type	Front-wheel drive
Clutch	Hydraulically operated dual clutch (wet)
Transmission type	7-speed S tronic
Transmission ratio in 1 <sup>st</sup> /2 <sup>nd</sup> gear	3.188 / 2.190
Transmission ratio in 3 <sup>rd</sup> /4 <sup>th</sup> gear	1.517 / 1.057
Transmission ratio in 5 <sup>th</sup> /6 <sup>th</sup> gear	0.738 / 0.557
Transmission ratio in 7 <sup>th</sup> /8 <sup>th</sup> gear	0.433 / -
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.750 / 4.410 / -

# Suspension / steering / brakes

Type and design of front-axle suspension	5-link front axle
Type and design of rear-axle suspension	5-link rear axle
Tires (basic)	205 / 60 R 17
Wheels (basic)	Cast aluminum flow forming 7 J x 17
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	15.2
Turning circle in m <i>(ft)</i>	12.1 (39.7)
Brake system	ESC/ABS/EBD, brake booster, hydraulic brake assist; Front: floating calipers; Rear: floating calipers and calipers with integrated electronic parking brake
Brake disk diameter front / rear in mm (in)	323 (12.7) / 300 (11.8)

# Performance / fuel

Top speed in km/h ( <i>mph</i> )	248 (154.1)
Acceleration, 0-100 km/h (0-62.1 mph)	7.8
Fuel type / octane value / fuel standard	Gasoline / 95 / DIN EN 228

# Consumption / emission\*

Fuel consumption, combined in l/100 km (US mpg)	7.5 - 6.6 (31.4 - 35.6)
CO2 emissions, combined in g/km (g/mi)	171 - 151 (275.2 - 243.0)
CO <sub>2</sub> class	F-E

# Servicing / guarantee (Germany)

Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	17 / 24 / 24

# Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb)</i>	1695 (3736.8) / 1770 (3902.2) / 2295 (5059.6)
Front / rear axle load limit in kg <i>(lb)</i>	1195 (2634.5) / 1200 (2645.5)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg <i>(lb)</i>	1700 (3747.9) / 1500 (3306.9) // 750 (1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	90 (198.4) / 80 (176.4)

# Capacities

Cooling system capacity (incl. heating) in l (US gal)	12.5 (3.3)
Engine oil capacity, including filter (change volume) in l ( <i>US qt</i> )	6 (6.3)
Fuel tank capacity / optional in l (US gal)	56 (14.8) /

4.8) / -

Dimensions**	* / body
--------------	----------

Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 5 / 5
Drag coefficient $C_d$ / frontal area A in m <sup>2</sup> (sq ft)	0.27 / 2.30 (24.8)
Vehicle height from - to in mm <i>(ft)</i>	1410 - 1461 (4.6 - 4.8)
Vehicle length from - to in mm <i>(ft)</i>	4829 - 4835 (15.8 - 15.9)
Vehicle width, without mirrors, from - to in mm ( <i>ft</i> )	1860 - 1860 (6.1 - 6.1)
Vehicle width, including mirrors, in mm ( <i>ft</i> )	2099 (6.9)
Wheelbase (full load) from - to // track width front/rear in mm ( <i>ft</i> )	2897 - 2902 (9.5 - 9.5) // 1624 (5.3) / 1611 (5.3)
Overhang angle, front / rear in degrees	14.1 / 18.5
Height of loading edge from - to in mm (ft)	640 - 672 (2.1 - 2.2)
Luggage compartment behind the 2 <sup>nd</sup> seat row in l ( <i>cu ft</i> )	445 (15.7)
Largest luggage capacity behind the 1 <sup>st</sup> seat row in l ( <i>cu ft</i> )	1299 (45.9)

\*Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO<sub>2</sub> emissions and performance figures.

\*\*Value range taking into account different chassis and equipment lines in relation to the basic model.