

Audi A6 Sportback



e-tron performance

Drivetrain / transmission / battery

Drive type	Rear-wheel drive
Number of electric motors front axle / rear axle	0 / 1
Max. output in kW	270
Electrical maximum output in kW	270
Max. output in launch control mode in kW	280
Electrical torque output front / rear in Nm (<i>lb-ft</i>)	- / 565 (<i>416.7</i>)
Battery type / number of cells	Lithium-Ion / 180
Gross / net battery capacity in kWh	100 / 94.9
Max. charging capacity AC / DC in kW	11 / 270
Charging time DC 10-80% in min	21
Charging time AC 0-100%, 3ph 16A@230V in min	600
On-board voltage 1 in volts	12
Voltage level of the HV battery in volts	800

Suspension / steering / brakes

Type and design of front-axle suspension	5-link front axle
Type and design of rear-axle suspension	5-link rear axle
Tires (basic)	225 / 55 R 19 245 / 50 R 19
Wheels (basic)	Forged aluminum 8 J x 19 Forged aluminum 8.5 x 19
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	16.4
Turning circle in m (<i>ft</i>)	12.3 (<i>40.4</i>)
Brake system	ESC/ABS/EBD/ brake unit, hydraulic brake assist; front: aluminum fixed caliper; rear: floating caliper with integrated electronic parking brake
Brake disk diameter front / rear in mm (<i>in</i>)	350 (<i>13.8</i>) / 350 (<i>13.8</i>)

Performance / range

Top speed in km/h (<i>mph</i>)	210 (<i>130.5</i>) (governed)
electrical acceleration, 0-100 km/h (<i>62.1 mph</i>) in s	5.4
Electrical range, combined in km (<i>mi</i>)	673 - 756 (<i>418.2 - 469.8</i>)

Consumption / emission*

Electric power consumption, combined in kWh/100 km (<i>62.1 mi</i>)	15.9 - 14.0
CO ₂ emissions, combined in g/km (<i>g/mi</i>)	0
CO ₂ class	A

Servicing / guarantee (Germany)

Service interval	2 years
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	19 / 26 / 26

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	2175 / 2250 / 2750 (4795.1 / 4960.4 / 6062.7)
Front / rear axle load limit in kg (<i>lb</i>)	1220 / 1580 (2689.6 / 3483.3)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	2100 / 2100 // 750 (4629.7 / 4629.7 // 1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	100 / 100 (220.5 / 220.5)

Dimensions / body**

Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 5/ 5
Drag coefficient C_d / frontal area A in m ² (<i>sq ft</i>)	0.21 / 2.46 (26.5)
Vehicle height from - to in mm (<i>ft</i>)	1455 - 1500 (4.8 - 4.9)
Vehicle length from - to in mm (<i>ft</i>)	4928 - 4928 (16.2 - 16.2)
Vehicle width, without mirrors, from - to in mm (<i>ft</i>)	1923 - 1923 (6.3 - 6.3)
Vehicle width, including mirrors, in mm (<i>ft</i>)	2137 (7.0 - 7.0)
Wheelbase (full load) from - to // track width front/rear in mm (<i>ft</i>)	2950 - 2951 (9.7 - 9.7) // 1661 (5.4) / 1623 (5.3)
Height of loading edge from - to in mm (<i>ft</i>)	640 - 672 (2.1 - 2.2)
Luggage compartment behind the 2 nd seat row in l (<i>cu ft</i>)	1330 (47.0)

*Information on fuel/power consumption and CO₂ emissions in ranges depending on the chosen equipment level of the car.

**Value range taking into account different chassis and equipment lines in relation to the basic model.