

# Audi A3 allstreet



TFSI e S tronic 150 kW

## Engine / electrics

Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1498 / 74.5 x 85.9 / 11.5
Max. power output in kW (PS) / at rpm	110 (150) / 5000 - 6000
Max. torque in Nm ( <i>lb-ft</i> ) / at rpm	250 (184.4) / 1500 - 4000
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emission standard	Euro 6e
Charging time AC 0-100%, 3ph 16A@230V in min	150
Max. charging capacity AC in kW	11
On-board voltage 1 in volts	12
Voltage level of the HV battery in volts	400

## Hybrid

Battery type (high-voltage) / number of cells	Lithium-Ion / 96
Gross / net battery capacity in kWh	25.7 / 19.7
Max. system output in kW (PS)	150 (204)
Peak electrical output in kW	85
Continuous electrical output in kW	55
Total system torque output in Nm ( <i>lb-ft</i> )	350 (258.1)
Electrical torque output in Nm ( <i>lb-ft</i> )	330 (243.4)

## Drivetrain / transmission

Drive type	Front-wheel drive
Clutch	Hydraulically actuated dual clutch (wet)
Transmission type	6-speed S tronic
Transmission ratio in 1 <sup>st</sup> /2 <sup>nd</sup> gear	3.500 / 2.773
Transmission ratio in 3 <sup>rd</sup> /4 <sup>th</sup> gear	1.852 / 1.020
Transmission ratio in 5 <sup>th</sup> /6 <sup>th</sup> gear	1.023 / 0.840
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.864 / 3.750 / 2.885

## Suspension / steering / brakes

Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	4-link rear axle
Wheels (basic) // Tires (basic)	Cast aluminum 7 J x 17 // 205 / 55 R 17
Steering	Electromechanical steering with speed-dependent power assistance
Steering ratio	14.9
Turning circle in m ( <i>ft</i> )	11.1 (36.4)
Brake system	Dual-circuit diagonal-split brake system with ESC/ABS/EBD, brake servo, hydraulic brake assist; Front: floating calipers; Rear: floating calipers with integrated electronic parking brake

---

**Performance / range**

Top speed / electrical in km/h ( <i>mph</i> )	225 (139.8) (limited) / 140 (87.0)
System acceleration, 0-100 km/h (0-62.1 <i>mph</i> )	7.4
Electrical range, City (EAER) in km ( <i>mi</i> )	167 - 185 (103.8 - 115.0)
Electrical range, combined (EAER) in km ( <i>mi</i> )	128 - 139 (79.5 - 86.4)
Fuel type / octane value / fuel standard	Electricity / Gasoline / 95 / DIN EN 228

---

**Consumption / emission\***

Electric power consumption, weighted combined in kWh/100 km (62.1 <i>mi</i> )	16.0 - 15.0
Fuel consumption, weighted combined in l/100 km ( <i>US mpg</i> )	0.4 - 0.3 (588.0 - 784.3)
Fuel consumption with discharged battery combined in l/100 km ( <i>US mpg</i> )	5.3 - 5.0
CO <sub>2</sub> emissions, weighted combined, in g/km ( <i>g/mi</i> )	8 - 7 (12.9 - 11.3)
CO <sub>2</sub> class, weighted combined	B
CO <sub>2</sub> class with discharged battery	D - C

---

**Servicing / guarantee (Germany)**

Service interval	30,000 km (18,641.1 <i>mi</i> ) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	14 / 20 / 22

---

**Weights / loads**

Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	1610 / 1685 / 2095 (3549.4 / 3714.8 / 4618.7)
Front / rear axle load limit in kg ( <i>lb</i> )	1080 / 1090 (2381.0 / 2403.0)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg ( <i>lb</i> )	1700 / 1400 // 750 (3747.9 / 3086.5 // 1653.5)
Roof load limit / permissible nose weight in kg ( <i>lb</i> )	75 / 80 (165.3 / 176.4)

---

**Capacities**

Cooling system capacity (incl. heating) in l ( <i>US gal</i> )	16.2 (4.3)
Engine oil capacity, including filter (change volume) in l ( <i>US qt</i> )	4.3 (4.5)
Fuel tank capacity / optional in l ( <i>US gal</i> )	40 (10.6) / -

---

**Dimensions\*\* / body**

Body type / number of doors / number of seats	Unitary steel / 5 / 5
Drag coefficient $C_d$ / frontal area A in m <sup>2</sup> (sq ft)	0.32 / 2.19 (23.6)
Vehicle height from - to in mm (ft)	1457 - 1486 (4.8 - 4.9)
Vehicle length from - to in mm (ft)	4353 - 4353 (14.3 - 14.3)
Vehicle width, without mirrors, from - to in mm (ft)	1816 - 1816 (6.0 - 6.0)
Vehicle width, including mirrors, in mm (ft)	1984 (6.5)
Wheelbase (full load) from - to // track width front/rear in mm (ft)	2628 - 2630 (8.6 - 8.6) // 1553 / 1523 (5.1/5.0)
Overhang angle, front / rear in degrees	15.0 / 26.8
Height of loading edge from - to in mm (ft)	697 - 705 (2.3 - 2.3)
Luggage compartment behind the 2 <sup>nd</sup> seat row in l (cu ft)	280 (9.9)
Largest luggage capacity behind the 1 <sup>st</sup> seat row in l (cu ft)	1100 (38.8)

\*Information on fuel/power consumption and CO<sub>2</sub> emissions in ranges depending on the chosen equipment level of the car.

\*\*Value range taking into account different chassis and equipment lines in relation to the basic model.