

# Audi A3 allstreet



TFSI e S tronic 150 kW

## Engine / electrics

|  |  |
|--|--|
| Engine type  | Inline 4-cylinder engine   |
| Valve gear / number of valves per cylinder             | Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 1498 / 74.5 x 85.9 / 11.5  |
| Max. power output in kW (PS) / at rpm                  | 110 (150) / 5000 – 6000  |
| Max. torque in Nm (lb-ft) / at rpm                     | 250 (184.4) / 1500 – 4000  |
| Mixture preparation                                    | Direct injection, lambda control, knock control, turbocharger, intercooler   |
| Exhaust emission control                               | Catalytic converter, oxygen sensor, gasoline particulate filter  |
| Emission standard                                      | Euro 6e-bis  |
| Charging time AC 0-100%, 3ph 16A@230V in min           | 150  |
| DC charging in kW                                      | 40   |
| Max. charging capacity AC in kW                        | 11   |
| On-board voltage 1 in volts                            | 12   |
| Voltage level of the HV battery in volts               | 400  |

## Hybrid

|   |                  |
|---|------------------|
| Battery type (high-voltage) / number of cells | Lithium-Ion / 96 |
| Gross / net battery capacity in kWh           | 25.7 / 19.7      |
| Max. system output in kW (PS)                 | 150 (204)        |
| Peak electrical output in kW                  | 85               |
| Continuous electrical output in kW            | 55               |
| Total system torque output in Nm (lb-ft)      | 350 (258.1)      |
| Electrical torque output in Nm (lb-ft)        | 330 (243.4)      |

## Drivetrain / transmission

|   |  |
|---|--|
| Drive type  | Front-wheel drive                        |
| Clutch  | Hydraulically actuated dual clutch (wet) |
| Transmission type   | 6-speed S tronic                         |
| Transmission ratio in 1 <sup>st</sup> /2 <sup>nd</sup> gear | 3.500 / 2.773                            |
| Transmission ratio in 3 <sup>rd</sup> /4 <sup>th</sup> gear | 1.852 / 1.020                            |
| Transmission ratio in 5 <sup>th</sup> /6 <sup>th</sup> gear | 1.023 / 0.840                            |
| Reverse gear ratio / final drive ratio 1-2 / 2-3            | 2.864 / 3.750 / 2.885                    |

---

## Suspension / steering / brakes

|  |  |
|--|--|
| Type and design of front-axle suspension | McPherson struts, front  |
| Type and design of rear-axle suspension  | 4-link rear axle   |
| Wheels (basic) // Tires (basic)          | Cast aluminum 7 J x 17 // 205 / 55 R 17  |
| Steering                                 | Electromechanical steering with speed-dependent power assistance   |
| Steering ratio                           | 14.9   |
| Turning circle in m (ft)                 | 11.1 (36.4)  |
| Brake system                             | Dual-circuit diagonal-split brake system with ESC/ABS/EBD, brake servo, hydraulic brake assist; Front: floating calipers; Rear: floating calipers with integrated electronic parking brake |

---

## Performance / range

|  |  |
|--|--|
| Top speed / electrical in km/h (mph)         | 225 (139.8) / 140 (87.0)                 |
| System acceleration, 0–100 km/h (0–62.1 mph) | 7.4                                      |
| Electrical range, City (EAER) in km (mi)     | 160 – 176 (99.4 – 109.4)                 |
| Electrical range, combined (EAER) in km (mi) | 128 – 139 (79.5 – 86.4)                  |
| Fuel type / octane value / fuel standard     | Electricity / Gasoline / 95 / DIN EN 228 |

---

## Consumption / emission<sup>1</sup>

|   |                           |
|---|---------------------------|
| Fuel consumption, weighted combined, in l/100 km (US mpg)                   | 1.4 – 1.2 (168.0 – 196.0) |
| Electric power consumption, weighted combined, in kWh/100 km (62.1 mi)      | 12.9 – 12.4               |
| CO <sub>2</sub> emissions, weighted combined, in g/km (g/mi)                | 31 – 26 (49.9 – 41.8)     |
| CO <sub>2</sub> class, weighted combined                                    | B                         |
| Fuel consumption with discharged battery, combined, in l/100 km (US mpg)    | 5.3 – 5.0                 |
| CO <sub>2</sub> emissions with discharged battery, combined, in g/km (g/mi) | 120 – 113 (193.1 – 181.9) |
| CO <sub>2</sub> class with discharged battery                               | D – C                     |

---

## Servicing / guarantee (Germany)

|   |  |
|---|--|
| Service interval  | 30,000 km (18,641.1 mi) / 2 years, whichever comes first |
| Vehicle / paint / rust perforation guarantee  | 2 / 3 / 12 years   |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 14 / 21 / 23   |

---

## Weights / loads

|   |  |
|---|--|
| Unladen weight without driver / with driver / gross weight limit in kg (lb) | 1610 / 1685 / 2095 (3549.4 / 3714.8 / 4618.7)  |
| Front / rear axle load limit in kg (lb)                                     | 1080 / 1090 (2381.0 / 2403.0)                  |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (lb)      | 1700 / 1400 // 750 (3747.9 / 3086.5 // 1653.5) |
| Roof load limit / permissible nose weight in kg (lb)                        | 75 / 80 (165.3 / 176.4)                        |

---

## Capacities

|  |               |
|--|---------------|
| Cooling system capacity (incl. heating) in l (US gal)              | 16.2 (4.3)    |
| Engine oil capacity, including filter (change volume) in l (US qt) | 4.3 (4.5)     |
| Fuel tank capacity / optional in l (US gal)                        | 40 (10.6) / - |

---

## Dimensions<sup>2</sup> / body

|   |  |
|---|--|
| Body type / number of doors / number of seats                             | Unitary steel / 5 / 5                            |
| Drag coefficient $C_d$ / frontal area A in m <sup>2</sup> (sq ft)         | 0.32 / 2.19 (23.6)                               |
| Vehicle height from – to in mm (ft)                                       | 1457 – 1486 (4.8 – 4.9)                          |
| Vehicle length from – to in mm (ft)                                       | 4353 – 4353 (14.3 – 14.3)                        |
| Vehicle width, without mirrors, from – to in mm (ft)                      | 1816 – 1816 (6.0 – 6.0)                          |
| Vehicle width, including mirrors, in mm (ft)                              | 1984 (6.5)                                       |
| Wheelbase (full load) from – to // track width front/rear in mm (ft)      | 2628 – 2630 (8.6 – 8.6) // 1553 / 1523 (5.1/5.0) |
| Overhang angle, front / rear in degrees                                   | 15.0 / 26.8                                      |
| Height of loading edge from – to in mm (ft)                               | 697 – 705 (2.3 – 2.3)                            |
| Luggage compartment behind the 2 <sup>nd</sup> seat row in l (cu ft)      | 280 (9.9)  |
| Largest luggage capacity behind the 1 <sup>st</sup> seat row in l (cu ft) | 1100 (38.8)                                      |

Program for Germany, Status: 12/15/25

<sup>1</sup> Information on fuel/power consumption and CO<sub>2</sub> emissions in ranges depending on the chosen equipment level of the car.  
<sup>2</sup> Value range taking into account different chassis and equipment lines in relation to the basic model.