

Audi Q5 SUV



TFSI e-hybrid quattro S tronic 220 kW

Engine / electrics

Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 10.5
Max. power output in kW (PS) / at rpm	185 (252) / 5000 - 6500
Max. torque in Nm (<i>lb-ft</i>) / at rpm	380 (280.3) / 1600 - 4500
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emission standard	Euro 6e-bis
Charging time AC 0-100%, 3ph 16A@230V in min	150
Max. charging capacity AC in kW	11
Max. electrical output at 12V in kW	3
On-board voltage 1 in volts	12
Voltage level of the HV battery in volts	400

Hybrid

Battery type (high-voltage) / number of cells	Lithium-Ion / 102
Gross / net battery capacity in kWh	25.9 / 20.7
Max. system output in kW (PS)	220 (299)
Continuous electrical output in kW	55
Total system torque output in Nm (<i>lb-ft</i>)	450 (331.9)
Electrical torque output in Nm (<i>lb-ft</i>)	350 (258.1)

Drivetrain / transmission

Drive type	quattro all-wheel drive with ultra technology
Clutch	Hydraulically operated dual clutch (wet)
Transmission type	7-speed S tronic
Transmission ratio in 1 st /2 nd gear	3.188 / 2.190
Transmission ratio in 3 rd /4 th gear	1.517 / 1.057
Transmission ratio in 5 th /6 th gear	0.738 / 0.557
Transmission ratio in 7 th /8 th gear	0.433 / -
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.750 / 5.302 / -

Suspension / steering / brakes

Type and design of front-axle suspension	5-link front axle
Type and design of rear-axle suspension	5-link rear axle
Wheels (basic) // Tires (basic)	Cast aluminum 8 J x 18 // 235 / 60 R 18
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	15.2
Turning circle in m (<i>ft</i>)	12 (39.4)
Brake system	ESC/ABS/EBD, brake unit, hydraulic brake assist; Front: floating calipers; Rear: floating calipers with integrated electronic parking brake
Brake disk diameter front / rear in mm (<i>in</i>)	360 / 330 (14.2 / 13.0)

Performance / range

Top speed / electrical in km/h (<i>mph</i>)	250 (155.3) (limited) / 140 (87.0)
System acceleration, 0-100 km/h (0-62.1 <i>mph</i>)	6.2
Electrical range, City (EAER) in km (<i>mi</i>)	95 - 113 (59.0 - 70.2)
Electrical range, combined (EAER) in km (<i>mi</i>)	82 - 100 (51.0 - 62.1)
Fuel type / octane value / fuel standard	Electricity / Gasoline / 95 / DIN EN 228

Consumption / emission*

Electric power consumption, weighted combined in kWh/100 km (62.1 <i>mi</i>)	16.8 - 15.5
Fuel consumption, weighted combined in l/100 km (<i>US mpg</i>)	3.3 - 2.5 (71.3 - 94.1)
Fuel consumption with discharged battery combined in l/100 km (<i>US mpg</i>)	8.3 - 7.2 (28.3 - 32.7)
CO ₂ emissions, weighted combined, in g/km (<i>g/mi</i>)	75 - 56 (120.7 - 90.1)
CO ₂ class, weighted combined	B
CO ₂ class with discharged battery	G - F

Servicing / guarantee (Germany)

Service interval	30,000 km (18,641.1 <i>mi</i>) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	20 / 28 / 25

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	2150 / 2225 / 2735 (4739.9 / 4905.3 / 6029.6)
Front / rear axle load limit in kg (<i>lb</i>)	1295 / 1525 (2855.0 / 3362.0)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	2000 / 2000 // 750 (4409.2 / 4409.2 // 1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	50 / 100 (110.2 / 220.5)

Capacities

Cooling system capacity (incl. heating) in l (<i>US gal</i>)	20.1 (5.3)
Engine oil capacity, including filter (change volume) in l (<i>US qt</i>)	6 (6.3)
Fuel tank capacity / optional in l (<i>US gal</i>)	55 (14.5) / -

Dimensions** / body	
Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 5 / 5
Drag coefficient C_d / frontal area A in m ² (sq ft)	0.31 / 2.64 (28.4)
Vehicle height from - to in mm (ft)	1614 - 1668 (5.3 - 5.5)
Vehicle length from - to in mm (ft)	4717 - 4717 (15.5 - 15.5)
Vehicle width, without mirrors, from - to in mm (ft)	1900 - 1900 (6.2 - 6.2)
Vehicle width, including mirrors, in mm (ft)	2155 (7.1)
Wheelbase (full load) from - to // track width front/rear in mm (ft)	2823 - 2827 (9.3 - 9.3) // 1621 (5.3) / 1613 (5.3)
Overhang angle, front / rear in degrees	17.1 / 24.7
Height of loading edge from - to in mm (ft)	757 - 777 (2.5 - 2.5)
Luggage compartment behind the 2 nd seat row in l (cu ft)	438 (15.5)
Largest luggage capacity behind the 1 st seat row in l (cu ft)	1358 (48.0)

*Information on fuel/power consumption and CO₂ emissions in ranges depending on the chosen equipment level of the car.

**Value range taking into account different chassis and equipment lines in relation to the basic model.