Audi RS 3 Sportback



TFSI

| Engine / electrics | |
|---|--|
| Engine type | Inline 5-cylinder engine |
| Valve gear / number of valves per cylinder | Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve- play compensation / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 2480 / 82.5 x 92.8 / 10.0 |
| Max. power output in kW (PS) / at rpm | 294 (400) / 5600 - 7000 |
| Max. torque in Nm (lb-ft) / at rpm | 500 (368.8) / 2250 - 5600 |
| Mixture preparation | Direct injection, lambda control, knock control, turbocharger, intercooler |
| Exhaust emission control | Catalytic converter, oxygen sensor, gasoline particulate filter |
| Emission standard | Euro 6d-ISC-FCM |
| Max. electrical output at 12V in kW | 2.2 |
| On-board voltage 1 in volts | 12 |
| Drivetrain / transmission | _ |
| Drive type | |
| Type of rear axle differential | Standard |
| Clutch | Hydraulically operated dual clutch (wet) |
| Transmission type | 7-speed S tronic |
| Transmission ratio in 1st/2nd gear | 3.560 / 2.530 |
| Transmission ratio in 3 rd /4 th gear | 1.680 / 1.020 |
| Transmission ratio in 5 th /6 th gear | 0.790 / 0.760 |
| Transmission ratio in 7 th /8 th gear | 0.630/- |
| Reverse gear ratio / final drive ratio 1-2 / 2-3 | |
| neverse gear radio / milat unive latio 1-2 / 2-3 | 2.790 / 4.059 / - |
| | 2.790 / 4.059 / - |
| Suspension / steering / brakes Type and design of front-axle suspension | 2.790 / 4.059 / - McPherson struts, front |
| Suspension / steering / brakes | |
| Suspension / steering / brakes Type and design of front-axle suspension | McPherson struts, front |
| Suspension / steering / brakes Type and design of front-axle suspension Type and design of rear-axle suspension | McPherson struts, front Four-link rear suspension |
| Suspension / steering / brakes Type and design of front-axle suspension Type and design of rear-axle suspension Tires (basic) | McPherson struts, front Four-link rear suspension 265 / 30 ZR 19 245 / 35 ZR 19 245 / 35 ZR 19 |
| Suspension / steering / brakes Type and design of front-axle suspension Type and design of rear-axle suspension Tires (basic) Wheels (basic) | McPherson struts, front Four-link rear suspension 265 / 30 ZR 19 245 / 35 ZR 19 245 / 35 ZR 19 Cast aluminum 9 J x 19 Cast aluminum 8 J x 19Cast aluminum 8 J x 19 |
| Suspension / steering / brakes Type and design of front-axle suspension Type and design of rear-axle suspension Tires (basic) Wheels (basic) Steering | McPherson struts, front Four-link rear suspension 265 / 30 ZR 19 245 / 35 ZR 19 245 / 35 ZR 19 Cast aluminum 9 J x 19 Cast aluminum 8 J x 19 Electromechanical progressive steering with speed-dependent power assistance |
| Suspension / steering / brakes Type and design of front-axle suspension Type and design of rear-axle suspension Tires (basic) Wheels (basic) Steering Steering ratio | McPherson struts, front Four-link rear suspension 265 / 30 ZR 19 245 / 35 ZR 19 245 / 35 ZR 19 Cast aluminum 9 J x 19 Cast aluminum 8 J x 19Cast aluminum 8 J x 19 Electromechanical progressive steering with speed-dependent power assistance 10.5 |
| Suspension / steering / brakes Type and design of front-axle suspension Type and design of rear-axle suspension Tires (basic) Wheels (basic) Steering Steering ratio Turning circle in m (ft) | McPherson struts, front Four-link rear suspension 265 / 30 ZR 19 245 / 35 ZR 19 245 / 35 ZR 19 Cast aluminum 9 J x 19 Cast aluminum 8 J x 19Cast aluminum 8 J x 19 Electromechanical progressive steering with speed-dependent power assistance 10.5 12 (39.4) ESC/ABS/EBD electromechanical brake booster with active accumulator; front: aluminum |
| Suspension / steering / brakes Type and design of front-axle suspension Type and design of rear-axle suspension Tires (basic) Wheels (basic) Steering Steering ratio Turning circle in m (ft) Brake system | McPherson struts, front Four-link rear suspension 265 / 30 ZR 19 245 / 35 ZR 19 245 / 35 ZR 19 Cast aluminum 9 J x 19 Cast aluminum 8 J x 19Cast aluminum 8 J x 19 Electromechanical progressive steering with speed-dependent power assistance 10.5 12 (39.4) ESC/ABS/EBD electromechanical brake booster with active accumulator; front: aluminum fixed calipers; rear: floating calipers with integrated parking brake |
| Suspension / steering / brakes Type and design of front-axle suspension Type and design of rear-axle suspension Tires (basic) Wheels (basic) Steering Steering ratio Turning circle in m (ft) Brake system Brake disk diameter front / rear in mm (in) | McPherson struts, front Four-link rear suspension 265 / 30 ZR 19 245 / 35 ZR 19 245 / 35 ZR 19 Cast aluminum 9 J x 19 Cast aluminum 8 J x 19Cast aluminum 8 J x 19 Electromechanical progressive steering with speed-dependent power assistance 10.5 12 (39.4) ESC/ABS/EBD electromechanical brake booster with active accumulator; front: aluminum fixed calipers; rear: floating calipers with integrated parking brake |

Gasoline / 98 / DIN EN 228

Fuel type / octane value / fuel standard

| Consumption / emission* | |
|---|--|
| Fuel consumption, combined according to WLTP in V100 km (US mpg) | 9.5 - 9.0 (24.8 - 26.1) |
| CO ₂ emissions, combined according to WLTP in g/km (g/mi) | 216 - 205 (347.6 - 329.9) |
| Servicing / guarantee (Germany) | |
| Service interval | 30,000 km (18,641.1 mi) / 2 years, whichever comes first |
| Vehicle / paint / rust perforation guarantee | 2 / 3 / 12 years |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 14/26/27 |
| Weights / loads | |
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 1570 (3461.3) / 1645 (3626.6) / 2070 (4563.6) |
| Front / rear axle load limit in kg (lb) | 1100 (2425.1) / 1075 (2347.9) |
| Roof load limit / permissible nose weight in kg (lb) | 75 (165.3) / - |
| Capacities | |
| Cooling system capacity (incl. heating) in l (US gal) | 9.8 (2.6) |
| Engine oil capacity, including filter (change volume) in l (US qt) | 7.1 (7.5) |
| Fuel tank capacity / optional in l (US gal) | 55 (14.5) / - |
| Dimensions** / body | |
| Body type / number of doors / number of seats | Unitary steel / 5 / 5 |
| Drag coefficient C _d / frontal area A in m² (sq ft) | 0.34 / 2.22 (23.9) |
| Vehicle height from - to in mm (ft) | 1436 (4.7) |
| Vehicle length from - to in mm (ft) | 4389 (14.4) |
| Vehicle width, without mirrors, in mm (ft) | 1851 (6.1) |
| Vehicle width, including mirrors, in mm (ft) | 1984 (6.5) |
| Wheelbase (full load) from - to // track width front/rear in mm (ft) | 2631 (8.6) // 1592 / 1524 (5.2 / 5.0) |
| Height of loading edge in mm (ft) | 659 (2.2) |
| Luggage compartment behind the 2^{nd} seat row in l (cu ft) | 282 (10.0) |
| Largest luggage capacity behind the 1st seat row in l (cu ft) | 1104 (39.0) |

*Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO₂ emissions and performance figures.

Consumption and emissions values are only available according to WLTP and not according to NEDC for this vehicle.

**Value range taking into account different chassis (steel spring and air spring) and equipment lines in relation to the basic model.