# Audi TT RS Roadster



TFSI

## Engine / electrics

Engine type	R 5 engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	2480 / 82.5 x 92.8 / 10.0
Max. power output in kW (PS) / at rpm	294 (400) / 5850 - 7000
Max. torque in Nm <i>(lb-ft) /</i> at rpm	480 ( <i>354.0</i> ) / 2250 - 5850
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emission standard	Euro 6d-ISC-FCM
Max. electrical output at 12V in kW	2.1
On-board voltage 1 in volts	12

## Drivetrain / transmission

Drive type	All-wheel drive
Clutch	Dual clutch
Transmission type	7-speed S tronic
Transmission ratio in 1 <sup>st</sup> /2 <sup>nd</sup> gear	3.563 / 2.526
Transmission ratio in 3 <sup>rd</sup> /4 <sup>th</sup> gear	1.679 / 1.022
Transmission ratio in 5 <sup>th</sup> /6 <sup>th</sup> gear	0.788 / 0.761
Transmission ratio in 7 <sup>th</sup> /8 <sup>th</sup> gear	0.635 / -
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.789 / - / -

## Suspension / steering / brakes

Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	4-link rear axle
Tires (basic)	245/35 R 19
Wheels (basic)	Cast aluminum flow forming 9 J x 19
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	14.6
Turning circle in m <i>(ft)</i>	11 (36.1)
Brake system	Dual-circuit diagonal-split brake system with ESC/ABS/EBD, hydraulic brake assist; Front: aluminum fixed calipers, internally ventilated brake discs; Rear: floating calipers with integrated electronic parking brake

# Performance / fuel / acoustics

Top speed in km/h ( <i>mph</i> )	250 (155.3) (governed)
Acceleration, 0-100 km/h (0-62.1 mph)	3.9
Fuel type / octane value / fuel standard	Gasoline / 98 / DIN EN 228

Consumption / emission*	
Fuel consumption, combined according to WLTP in I/100 km (US mpg)	9.3 - 9.2 (25.3 - 25.6)
CO <sub>2</sub> emissions, combined according to WLTP in g/km (g/mi)	210 - 208 (338.0 - 334.7)
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	12 / 26 / 25
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg ( <i>lb</i> )	1565 (3450.2) / 1640 (3615.6) / 1850 (4078.6)
Front / rear axle load limit in kg <i>(lb)</i>	1070 (2358.9) / 815 (1851.9)
Capacities	
Cooling system capacity (incl. heating) in l (US gal)	9.1 (2.4)
Engine oil capacity, including filter (change volume) in l <i>(US qt)</i>	7.1 (7.5)
Fuel tank capacity / optional in l (US gal)	55 (14.5) / -
Dimensions / body	
Body type / number of doors / number of seats	Audi Space Frame (ASF) / 2 / 2
Standard dimensions (length / width excluding mirrors / height with steel springs / air springs) in mm ( <i>ft</i> )	4201 ( <i>13.8</i> ) / 1832 ( <i>6.0</i> ) / 1346 ( <i>4.4</i> ) / -
Wheelbase // track width front/rear in mm ( <i>ft</i> )	2505 (8.22) // 1564 (5.1) / 1543 (5.1)
Height of loading edge in mm <i>(ft)</i>	803 (2.6)
Closed luggage compartment - behind the 2 <sup>nd</sup> seat row in l ( <i>cu ft</i> )	280 (9.9)

\*Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and erodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO<sub>2</sub> emissions and performance figures.