Audi RS 3 Sedan



TFSI

	_
Engine / electrics	
Engine type	Inline 5-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve- play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	2480 / 82.5 x 92.8 / 10.0
Max. power output in kW (PS) / at rpm	294 (400) / 5600 - 7000
Max. torque in Nm (lb-ft) / at rpm	500 (368.8) / 2250 - 5600
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emission standard	Euro 6d-ISC-FCM
Max. electrical output at 12V in kW	2.2
On-board voltage 1 in volts	12
Drivetrain / transmission	_
Drive type	All-wheel drive
Type of rear axle differential	Standard
Clutch	Hydraulically operated dual clutch (wet)
Transmission type	7-speed S tronic
Transmission ratio in 1st/2nd gear	3.560 / 2.530
Transmission ratio in 3 rd /4 th gear	1.680 / 1.020
Transmission ratio in 5 th /6 th gear	0.790 / 0.760
Transmission ratio in 7 th /8 th gear	0.630 / -
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.790 / 4.059 / -
Suspension / steering / brakes	_
Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Four-link rear suspension
Tires (basic)	265 / 30 ZR 19 245 / 35 ZR 19 245 / 35 ZR 19
Wheels (basic)	Cast aluminum 9 J x 19 Cast aluminum 8 J x 19Cast aluminum 8 J x 19
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	10.5
Turning circle in m (ft)	12 (39.4)
Brake system	ESC/ABS/EBD electromechanical brake booster with active accumulator; front: aluminum fixed calipers; rear: floating calipers with integrated parking brake
Brake disk diameter front / rear in mm (in)	375 / 310 (14.8 / 12.2)
Performance / fuel	-
Top speed in km/h (mph)	250 (155.3) (governed)
Acceleration, 0-100 km/h (0-62.1 mph)	3.8

Gasoline / 98 / DIN EN 228

Fuel type / octane value / fuel standard

Consumption / emission*	
Fuel consumption, combined according to WLTP in V100 km (US mpg)	9.4 - 8.9 (25.0 - 26.4)
CO ₂ emissions, combined according to WLTP in g/km (g/mi)	214 - 201 (344.4 - 323.5)
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	14/26/27
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (lb)	1570 (3461.3) / 1645 (3626.6) / 2070 (4563.6)
Front / rear axle load limit in kg (lb)	1100 (2425.1) / 1065 (2347.9)
Roof load limit / permissible nose weight in kg (lb)	75 (165.3) / -
Capacities	
Cooling system capacity (incl. heating) in l (US gal)	9.8 (2.6)
Engine oil capacity, including filter (change volume) in l (US qt)	7.1 (7.5)
Fuel tank capacity / optional in l (US gal)	55 (14.5) / -
Dimensions** / body	
Body type / number of doors / number of seats	Unitary steel / 4 / 5
Drag coefficient C _d / frontal area A in m ² (sq ft)	0.32 / 2.22 (23.9)
Vehicle height from - to in mm (ft)	1412 (4.6)
Vehicle length from - to in mm (ft)	4542 (14.9)
Vehicle width, without mirrors, in mm (ft)	1851 (6.1)
Vehicle width, including mirrors, in mm (ft)	1984 (6.5)
Wheelbase (full load) from - to // track width front/rear in mm (ft)	2631 (8.6) // 1592 / 1524 (5.2 / 5.0)
Height of loading edge in mm (ft)	676 (2.2)
Luggage compartment behind the 2^{nd} seat row in l (cu ft)	321 (11.3)

*Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO₂ emissions and performance figures.

Consumption and emissions values are only available according to WLTP and not according to NEDC for this vehicle.

**Value range taking into account different chassis (steel spring and air spring) and equipment lines in relation to the basic model.