Audi RS 5 Coupé



TFSI

Engine / electrics

Engine type	V6 engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve- play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	2894 / 84.5 x 86.0 / 10.0
Max. power output in kW (PS) / at rpm	331 (450) / 5700 - 6700
Max. torque in Nm <i>(lb-ft) /</i> at rpm	600 (442.5) / 2000 - 5000
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emission standard	Euro 6d-ISC-FCM
Max. electrical output at 12V in kW	1.8
On-board voltage 1 in volts	12

Drivetrain / transmission

Drive type	quattro permanent all-wheel drive with self-locking center differential
Type of rear axle differential	Standard
Clutch	Hydraulic torque converter with lock-up clutch
Transmission type	8-speed tiptronic
Transmission ratio in 1 st /2 nd gear	5.000 / 3.200
Transmission ratio in 3 rd /4 th gear	2.143 / 1.720
Transmission ratio in 5 th /6 th gear	1.313 / 1.000
Transmission ratio in 7 th /8 th gear	0.823 / 0.640
Reverse gear ratio / final drive ratio 1-2 / 2-3	-3.478 / 3.204 / 1.000

Suspension / steering / brakes

5-link front axle
5-link rear axle
265 / 35 R 19
Forged aluminum 9 J x 19
Electromechanical steering with speed-dependent power assistance
15.9
11.6 (38.1)
Dual-circuit brake system with black/white split for front/rear axles; front: aluminum fixed calipers; rear: floating calipers with integrated electronic parking brake
375 / 330 (14.8 / 13.0)
_

Performance / fuel

Top speed in km/h (mph)	250 (<i>155.3</i>) (governed)
Acceleration, 0-100 km/h (0-62.1 mph)	3.9
Fuel type / octane value / fuel standard	Gasoline / 98 / DIN EN 228

Consumption / emission*	
Fuel consumption, combined according to WLTP in I/100 km (US mpg)	9.8 - 9.3 (24.0 - 25.3)
CO ₂ emissions, combined according to WLTP in g/km (g/mi)	223 - 211 (358.9 - 339.6)
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	15 / 29 / 30
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1695 (3736.8) / 1770 (3902.2) / 2210 (4872.2) / -
Front / rear axle load limit in kg (<i>lb</i>)	1205 (2656.6)/ 1100 (2425.1)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	75 (165.3) / -
Capacities	
Cooling system capacity (incl. heating) in l (US gal)	14.6 (3.9)
Engine oil capacity, including filter (change volume) in l (<i>US qt</i>)	7.6 (8.0)
Fuel tank capacity / optional in l (US gal)	58 (15.3) / -
Dimensions** / body	
Body type / number of doors / number of seats	Unitary steel/aluminum composite construction / 2 / 4
Drag coefficient C _d / frontal area A in m² (sq ft)	0.32 / 2.19 (23.6)
Vehicle height from - to in mm (<i>ft</i>)	1344 - 1380 (4.4 - 4.5)
Vehicle length from - to in mm (<i>ft</i>)	4717 - 4717 (15.5 - 15.5)
Vehicle width, without mirrors, in mm (ft)	1866 - 1866 (6.1 - 6.1)
Vehicle width, including mirrors, in mm (<i>ft</i>)	2029 (6.7)
Wheelbase (full load) from - to // track width front/rear in mm (<i>ft</i>)	2771 - 2771 (9.1 - 9.1) // 1598 (5.2) / 1588 (5.2)
Overhang angle, front / rear in degrees	11.0 / 17.1
Height of loading edge in mm (<i>ft</i>)	670 (2.2)
Luggage compartment behind the 2 nd seat row in l (<i>cu ft</i>)	450 (15.9)

*Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO₂ emissions and performance figures. Consumption and emissions values are only available according to WLTP and not according to NEDC for this vehicle.

**Value range taking into account different chassis (steel spring and air spring) and equipment lines in relation to the basic model.