

Audi A8



55 TFSI quattro tiptronic 250 kW MHEV

Engine / electrics

| | |
|--|---|
| Engine type | V6 engine |
| Valve gear / number of valves per cylinder | Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder |
| Displacement in cc / bore x stroke in mm / compression | 2995 / 84.5 x 89.0 / 11.2 |
| Max. power output in kW (PS) / at rpm | 250 (340) / 5000 - 6400 |
| Max. torque in Nm (<i>lb-ft</i>) / at rpm | 500 (368.8) / 1370 - 4500 |
| Mixture preparation | Direct injection, lambda control, knock control, turbocharger, intercooler |
| Exhaust emission control | Catalytic converter, oxygen sensor, gasoline particulate filter |
| Emission standard | Euro 6e |
| Max. electrical output at 12V in kW | 3 |
| On-board voltage 1 in volts | 12 |
| On-board voltage 2 in volts | 48 |

Drivetrain / transmission

| | |
|---|---|
| Drive type | quattro permanent all-wheel drive with self-locking center differential |
| Type of rear axle differential | Standard |
| Clutch | Hydraulic torque converter with lock-up clutch |
| Transmission type | 8-speed tiptronic |
| Transmission ratio in 1 st /2 nd gear | 4.714 / 3.143 |
| Transmission ratio in 3 rd /4 th gear | 2.106 / 1.667 |
| Transmission ratio in 5 th /6 th gear | 1.285 / 1.000 |
| Transmission ratio in 7 th /8 th gear | 0.839 / 0.667 |
| Reverse gear ratio / final drive ratio 1-2 / 2-3 | 3.317 / 3.076 / - |

Suspension / steering / brakes

| | |
|--|--|
| Type and design of front-axle suspension | 5-link front axle |
| Type and design of rear-axle suspension | 5-link rear axle |
| Tires (basic) | 235 / 55 R 18 |
| Wheels (basic) | Forged aluminum 8 J x 18 |
| Steering | Electromechanical progressive steering with speed-dependent power assistance |
| Steering ratio | 15.8 |
| Turning circle in m (<i>ft</i>) | 12.5 (41.0) |
| Brake system | ESC/ABS/EBD, brake booster, hydraulic brake assist; Front: aluminum fixed calipers; Rear: floating calipers with integrated electronic parking brake |
| Brake disk diameter front / rear in mm (<i>in</i>) | 375 (14.8) / 350 (13.8) |

Performance / fuel

| | |
|---|----------------------------|
| Top speed in km/h (<i>mph</i>) | 250 (155.3) (governed) |
| Acceleration, 0-100 km/h (0-62.1 <i>mph</i>) | 5.6 |
| Fuel type / octane value / fuel standard | Gasoline / 95 / DIN EN 228 |

Consumption / emission*

| | |
|---|---------------------------|
| Fuel consumption, combined in l/100 km (<i>US mpg</i>) | 10.3 - 9.3 (22.8 - 25.3) |
| CO ₂ emissions, combined in g/km (<i>g/mi</i>) | 235 - 211 (378.2 - 339.6) |
| CO ₂ class | G |

Servicing / guarantee (Germany)

| | |
|--|--|
| Service interval | depending on driving style between 15,000 km (9,320.6 mi) / 1 year and 30,000 km (18,641.1 mi) / 2 years |
| Vehicle / paint / rust perforation guarantee | 2 / 3 / 12 years |
| Insurance classification in Germany: third party / fully comprehensive / part-comprehensive | 20 / 29 / 30 |

Weights / loads

| | |
|--|---|
| Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>) | 1960 (4321.1) / 2035 (4486.4) / 2710 (5974.5) |
| Front / rear axle load limit in kg (<i>lb</i>) | 1360 (2998.3) / 1450 (3196.7) |
| Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>) | 2300 (5070.6) / 2300 (5070.6) // 750 (1653.5) |
| Roof load limit / permissible nose weight in kg (<i>lb</i>) | 90 (198.4) / 95 (209.4) |

Capacities

| | |
|---|---------------|
| Cooling system capacity (incl. heating) in l (<i>US gal</i>) | 12.1 (3.2) |
| Engine oil capacity, including filter (change volume) in l (<i>US qt</i>) | 7.6 (8.0) |
| Fuel tank capacity / optional in l (<i>US gal</i>) | 82 (21.7) / - |

Dimensions** / body

| | |
|---|--|
| Body type / number of doors / number of seats | Audi Space Frame (ASF) / 4 / 5 |
| Drag coefficient C _d / frontal area A in m ² (<i>sq ft</i>) | 0.26 / 2.43 (26.2) |
| Vehicle height from - to in mm (<i>ft</i>) | 1462 - 1487 (4.8 - 4.9) |
| Vehicle length from - to in mm (<i>ft</i>) | 5190 - 5190 (17.0 - 17.0) |
| Vehicle width, without mirrors, from - to in mm (<i>ft</i>) | 1945 - 1945 (6.4 - 6.4) |
| Vehicle width, including mirrors, in mm (<i>ft</i>) | 2130 (7.0) |
| Wheelbase (full load) from - to // track width front/rear in mm (<i>ft</i>) | 2998 - 2998 (9.8 - 9.8) // 1645 (5.4) / 1633 (5.4) |
| Overhang angle, front / rear in degrees | 11.0 / 14.8 |
| Height of loading edge from - to in mm (<i>ft</i>) | 691 - 701 (2.3 - 2.3) |
| Luggage compartment behind the 2 nd seat row in l (<i>cu ft</i>) | 505 (17.8) |

*Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO₂ emissions and performance figures.

**Value range taking into account different chassis and equipment lines in relation to the basic model.