

Technical Data		Audi A1 Sportback 30 TFSI (85 kW)
Program for Germany	Status: 9/21/2018	
Engine / electrics		
Engine type	Inline 3-cylinder engine	
Valve gear / number of valves per cylinder	- / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression	999 / 74.5 x 76.4 / 10.5	
Max. power output in kW (hp) / at rpm	85 (120) / 5000 - 5500	
Max. torque in Nm (lb-ft) / at rpm	200 (147.5) / 2000 - 3500	
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler	
Emissions standard	EU6	
Start-stop / REM	yes / yes	
Battery in A / Ah	320 / 59	
Max. electrical output at 12V in kilowatts	1.3	
On-board voltage 1 in volts	12	
On-board voltage 2 in volts	-	
Drivetrain / transmission		
Drive type	Front-wheel drive	
Transmission type	6-speed manual transmission / manual	
Transmission ratio in 1st/2nd gear	3.769 / 1.281	
Transmission ratio in 3rd/4th gear	1.281 / 0.973	
Transmission ratio in 5th/6th gear	0.778 / 0.642	
Reverse gear ratio / final drive ratio 1-2	3.182 / 3.789	
Suspension / steering / brakes		
Type and design of front-axle suspension	McPherson struts, front	
Type and design of rear-axle suspension	Compound link rear suspension	
Steering	Electromechanical steering with speed-dependent power assistance	
Turning circle / turning circle optional in m (ft)	10.5 (34.4) / -	
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Tires (basic)	185/65 R 15 92 V XL (Extra Load) -	
Wheels (basic)	Steel 5.5Jx15"	
Performance / consumption / acoustics		
Top speed in km/h (mph)	203 (126.1)	
Acceleration, 0-100 km/h (0-62.1 mph)	9.5	
Fuel type / octane value	Gasoline / 95	
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per ECE R51.03 in db (A)	73.9 / 68 / 65	
Fuel consumption / emissions (according to tire size)		
Tire package A		
Tire package A: designation	185/65 R15 92V, H9H	
Tire package A fuel consumption, urban/extra-urban/combined in liters per 100 kilometers (US mpg)	5.9 (39.9) / 4.1 (57.4) / 4.8 (49.0)	
Tire package A CO2 emissions urban/extra-urban/combined in grams per kilometer (g/mi)	134 (215.7) / 93 (149.7) / 108 (173.8)	
Tire package B		
Tire package B: designation	195/55 R16 91V, I09 215/45 R17 91W, I10 195/55 R16, Q13	
Tire package B fuel consumption, urban/extra-urban/combined in liters per 100 kilometers (US mpg)	6.0 (39.2) / 4.2 (56.0) / 4.9 (48.0)	
Tire package B CO2 emissions urban/extra-urban/combined in grams per kilometer (g/mi)	136 (218.9) / 95 (152.9) / 111 (178.6)	
Tire package C		
Tire package C: designation	215/40 R18 89Y, H9J	
Tire package C fuel consumption, urban/extra-urban/combined in liters per 100 kilometers (US mpg)	6.0 (39.2) / 4.2 (56.0) / 4.9 (48.0)	
Tire package C CO2 emissions urban/extra-urban/combined in grams per kilometer (g/mi)	136 (218.9) / 96 (154.5) / 111 (178.6)	

Servicing / guarantee (Germany)	
Service interval (mi)	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	14 / 17 / 17
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (lb)	1105 (2436.1) / 1180 (2601.5) / 1655 (3648.7)
Front/rear axle load limit in kg (lb)	880 (1940.1) / 805 (1774.7)
Roof load limit / permissible nose weight in kg (lb)	75 (165.3) / -
Capacities	
Cooling system capacity (incl. heating) in liters (US gal)	6.2 (1.6)
Engine oil capacity, including filter (change volume) in liters (US qt)	4 (4.2)
Fuel tank capacity in liters (US gal)	40 (10.6)
Dimensions / body	
Body type / number of doors	- / 4
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (sq ft)	0.31 / 2.07 (22.3)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (ft)	4029 (13.2) / 1740 (5.7) / 1433 (4.7) / -
Width including mirrors in mm (ft)	1940 (6.4)
Wheelbase / track width front/rear in mm (ft)	2563 (8.4) / 1524 (5.0) / 1501 (4.9)
Overhang angle of steel springs front/rear in degrees	16.50 / 12.40
Height of loading edge with steel springs / air springs in mm (ft)	668 (2.2) / -
Luggage capacity behind 2nd seat bench, open / closed in l (cu ft)	Not available / 335 (11.8)