Technical Data	Audi A1 Sportback 30 TFSI S tronic (85 kW)
Program for Germany	Status: 9/21/2018
Engine / electrics	
Engine type	Inline 3-cylinder engine
Valve gear / number of valves per cylinder	- / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	999 / 74.5 x 76.4 / 10.5
Max. power output in kW (hp) / at rpm	85 (120) / 5000 - 5500
Max. torque in Nm <i>(lb-ft) /</i> at rpm	200 / 2000 - 3500
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Emissions standard	EU6
Start-stop / REM	yes / yes
Battery in A / Ah	320 / 59
Max. electrical output at 12V in kilowatts	1.3
On-board voltage 1 in volts	12
On-board voltage 2 in volts	-
Drivetrain / transmission	
Drive type	Front-wheel drive
Clutch	Hydraulically actuated dry clutch, asbestos/lead-free linings, dual-mass flywheel
Transmission type	7-speed - / dual clutch
Transmission ratio in 1st/2nd gear	3.765 / 2.273
Transmission ratio in 3rd/4th gear	1.531 / 1.122
Transmission ratio in 5th/6th gear	1.176 / 0.951
Transmission ratio in 7th/8th gear	0.795 / -
Reverse gear ratio / final drive ratio 1-2	4.170 / 4.438
Suspension / steering / brakes	
Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Compound link rear suspension
Steering	Electromechanical steering with speed-dependent power assistance
Turning circle / turning circle optional in m (ft)	10.5 (34.4) / -
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic)	185/65 R 15 92 V XL (Extra Load) -
Wheels (basic)	Steel 5.5Jx15"
Performance / consumption / acoustics	
Top speed in km/h <i>(mph)</i>	203 (126.1)
Acceleration, 0-100 km/h (0-62.1 mph)	9.4
Fuel type / octane value	Gasoline / 95
Exterior noise level when stationary / drive-past as per ECE R51.02 / drive-past as per	73.9 / 68 / 65
ECE R51.03 in db (A)	13.9700703
Fuel consumption / emissions (according to tire size)	
Tire package A	
Tire package A: designation	185/65 R15 92V, H9H
Tire package A fuel consumption, urban/extra-urban/combined in liters per 100 kilometers (US mpg)	5.8 (40.6) / 4.2 (56.0) / 4.8 (49.0)
Tire package A CO2 emissions urban/extra-urban/combined in grams per kilometer (g/mi)	132 (212.4) / 95 (152.9) / 108 (173.8)
Tire package B	
Tire package B: designation	215/45 R17 91W, I10
Tire package B fuel consumption, urban/extra-urban/combined in liters per 100 kilometers (US mpg)	5.9 (39.9) / 4.2 (56.0) / 4.8 (49.0)
Tire package B CO2 emissions urban/extra-urban/combined in grams per kilometer (g/mi)	133 (214.0) / 96 (154.5) / 110 (177.0)
Tire package C	
Tire package C: designation	195/55 R16 91V, I09 195/55 R16, Q13
Tire package C fuel consumption, urban/extra-urban/combined in liters per 100 kilometers (US mpg)	5.9 (39.9) / 4.2 (56.0) / 4.8 (49.0)
Tire package C CO2 emissions urban/extra-urban/combined in grams per kilometer	

Tire package C CO2 emissions urban/extra-urban/combined in grams per kilometer (g/mi)	133 (214.0) / 97 (156.1) / 110 (177.0)
Tire package D	
Tire package D: designation	215/40 R18 89Y, H9J
Tire package D fuel consumption, urban/extra-urban/combined in liters per 100 kilometers (US mpg)	5.9 (39.9) / 4.3 (54.7) / 4.9 (48.0)
Tire package D CO2 emissions urban/extra-urban/combined in grams per kilometer (g/mi)	133 (214.0) / 97 (156.1) / 111 (178.6)

Servicing / guarantee (Germany)	
Service interval (mi)	30,000 km (18,641.1) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 (years)
Insurance classification in Germany: third party / fully comprehensive / part- comprehensive	14 / 17 / 17
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (Ib)	1125 (2480.2) / 1200 (2645.5) / 1680 (3703.8)
Front/rear axle load limit in kg (lb)	905 (1995.2) / 805 (1774.7)
Roof load limit / permissible nose weight in kg (Ib)	75 (165.3) / -
Capacities	
Cooling system capacity (incl. heating) in liters (US gal)	6.2 (1.6)
Engine oil capacity, including filter (change volume) in liters (US qt)	4 (4.2)
Fuel tank capacity in liters (US gal)	40 (10.6)
Dimensions / body	
Body type / number of doors	- / 4
Number of seats	5
Drag coefficient Cd / frontal area A in m <sup>2</sup> (sq ft)	0.31 / 2.07 (22.3)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm <i>(ft)</i>	4029 (13.2) / 1740 (5.7) / 1433 (4.7) / -
Width including mirrors in mm (ft)	1940 (6.4)
Wheelbase / track width front/rear in mm (ft)	2563 (8.4) / 1524 (5.0) / 1501 (4.9)
Overhang angle of steel springs front/rear in degrees	16.50 / 12.40
Height of loading edge with steel springs / air springs in mm (ft)	668 (2.2) / -
Luggage capacity behind 2nd seat bench, open / closed in I (cu ft)	Not available / 335 (11.8)