Audi Q2



35 TFSI S tronic 110 kW

Inline 4-cylinder engine
Roller cam follower, overhead camshafts, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
1498 / 74.5 x 85.9 / 12.0
110 (150) / 5000 - 6000
250 (184.4) / 1500 - 3500
Direct injection, lambda control, knock control, turbocharger, intercooler
Catalytic converter, oxygen sensor, gasoline particulate filter
Euro 6d-ISC-FCM
1.3
12
-
Front-wheel drive
2 hydraulically actuated dry clutches
7-speed S tronic
3.500 / 2.087
1.343 / 0.940
0.974 / 0.780
0.653 / -
3.722 / 4.800 / 3.429
-
McPherson struts, front
Torsion-beam rear axle
205 / 60 R 16
Steel 6 J x 16
Electromechanical progressive steering with speed-dependent power assistance
14.1
11.1 (36.4)
Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist; Front: floating caliper; Rear: floating caliper with integrated electronic parking brake
-
218 (135.5)

Gasoline / 95 / DIN EN 228

Fuel type / octane value / fuel standard

Consumption / emission*	
Fuel consumption, combined according to WLTP in I/100 km (US mpg)	6.7 - 6.0 (35.1 - 39.2)
CO ₂ emissions, combined according to WLTP in g/km (g/mi)	150 - 135 <i>(241.4 - 217.3)</i>
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	16 / 19 / 22
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (lb)	1305 (<i>2877.0</i>) / 1380 (<i>3042.4</i>) / 1870 (<i>4122.6</i>)
Front / rear axle load limit in kg (lb)	1000 (2204.6) / 960 (2116.4)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)	1700 (<i>3747.9</i>) / 1500 (<i>3306.9</i>) // 690 (<i>1521.2</i>)
Roof load limit / permissible nose weight in kg (lb)	60 (132.3) / 75 (165.3)
Capacities	
Cooling system capacity (incl. heating) in l (US gal)	11.5 (3.0)
Engine oil capacity, including filter (change volume) in l (US qt)	4.3 (4.5)
Fuel tank capacity / optional in l (US gal)	50 (13.2) / -
Dimensions** / body	
Body type / number of doors / number of seats	Unitary steel / 5 / 5
Drag coefficient C _d / frontal area A in m ² (sq ft)	0.32 / 2.29 (24.6)
Vehicle height from - to in mm (ft)	1503 - 1548 <i>(4.9 - 5.1)</i>
Vehicle length from - to in mm (ft)	4208 - 4216 (13.8 - 13.8)
Vehicle width, without mirrors, in mm (ft)	1794 - 1802 (5.9 - 5.9)
Vehicle width, including mirrors, in mm (ft)	2009 (6.6)
Wheelbase (full load) from - to // track width front/rear in mm (ft)	2589 - 2592 <i>(8.5 - 8.5)</i> // 1546 <i>(5.07)</i> / 1542 <i>(5.06)</i>
Overhang angle, front / rear in degrees	18.6 / 28.0
Height of loading edge in mm (ft)	740 (2.4)
Luggage compartment behind the 2 nd seat row in l (cu ft)	405 (14.3)

*Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO₂ emissions and performance figures.

Consumption and emissions values are only available according to WLTP and not according to NEDC for this vehicle.

Largest luggage capacity behind the 1st seat row in l (cu ft)

^{**}Value range taking into account different chassis (steel spring and air spring) and equipment lines in relation to the basic model.