Audi A4 Avant

35 TFSI S tronic 110 kW MHEV



Engine / electrics

Engine type	Inline 4-cylinder engine	
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve- play compensation / 2/2 inlet/exhaust valves per cylinder	
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 12.2	
Max. power output in kW (PS) / at rpm	110 (150) / 4000 - 6000	
Max. torque in Nm <i>(lb-ft) /</i> at rpm	270 (199.1) / 1350 - 3850	
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler	
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter	
Emission standard	Euro 6e	
Max. electrical output at 12V in kW	3.1	
On-board voltage 1 in volts	12	

Drivetrain / transmission

Drive type 	Front-wheel drive ————————————————————————————————————	
Transmission ratio in 1 st /2 nd gear	3.188 / 2.190	
Transmission ratio in 3 rd /4 th gear	1.517 / 1.057	
Transmission ratio in 5 th /6 th gear	0.738 / 0.557	
Transmission ratio in 7 th /8 th gear	0.433 / -	
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.750 / 4.234 / -	

Suspension / steering / brakes

Type and design of front-axle suspension	5-link front axle	
Type and design of rear-axle suspension	5-link rear axle	
Tires (basic)	205 / 60 R 16	
Wheels (basic)	Forged aluminum 7 J x 16	
Steering	Electromechanical steering with speed-dependent power assistance	
Steering ratio	15.9	
Turning circle in m <i>(ft)</i>	11.6 (38.1)	
Brake system	Dual-circuit brake system with black/white split for front/rear axles; front: floating calipers; rear: floating calipers with integrated electronic parking brake	
Brake disk diameter front / rear in mm (in)	314 (12.4) / 300 (11.8)	

Performance / fuel

Top speed in km/h (mph)	210 (130.5) (governed)
Acceleration, 0-100 km/h (0-62.1 mph)	9.2
Fuel type / octane value / fuel standard	Gasoline / 95 / DIN EN 228

Consumption / emission*

Fuel consumption, combined in l/100 km (US mpg)	7.5 - 6.4 (31.4 - 36.8)
CO2 emissions, combined in g/km (g/mi)	171 - 146 (275.2 - 235.0)
CO ₂ class	F-E

Servicing / guarantee (Germany)

Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first	
Vehicle / paint / rust perforation guarantee	2 / 3 / 12 years	
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	14/22/23	

Weights / loads

Unladen weight without driver / with driver / gross weight limit in kg (<i>lb)</i>	1520 (3351.0) / 1595 (3516.4) / 2115 (4662.8)
Front / rear axle load limit in kg (<i>lb</i>)	1065 (2347.9) / 1150 (2535.3)
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg <i>(lb)</i>	1700 (3747.9) / 1500 (3306.9) // 750 (1653.5)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	90 (198.4) / 80 (176.4)

Capacities

Cooling system capacity (incl. heating) in l (US gal)	8 (2.1)
Engine oil capacity, including filter (change volume) in l (<i>US qt)</i>	5.2 (5.5)
Fuel tank capacity / optional in l (US gal)	54 (14.3) / -

Dimensions** / body Body type / number of doors / number of seats Unitary steel/aluminum composite construction / 5 / 5 Drag coefficient C_d / frontal area A in m² (sq ft) 0.29 / 2.20 (23.7) 1415 - 1477 (4.6 - 4.8) Vehicle height from - to in mm (ft) Vehicle length from - to in mm (ft) 4762 - 4770 (15.6 - 15.6) 1847 - 1847 (6.1 - 6.1) Vehicle width, without mirrors, in mm (ft) Vehicle width, including mirrors, in mm (ft) 2022 (6.6) Wheelbase (full load) from - to // track width front/rear in 2826 - 2831 (9.3 - 9.3) // 1572 (5.2) / 1555 (5.1) mm (ft) Overhang angle, front / rear in degrees 15.2 / 17.8 Height of loading edge in mm (ft) 630 (2.1) Luggage compartment behind the 2nd seat row in l (*cu ft*) 495 (17.5)

Largest luggage capacity behind the 1st seat row in l (*cu ft*) 1495 (52.8)

*Additional equipment and accessories (attachments, tire size, etc.) may change relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, alongside weather and traffic conditions as well as individual driving style, may affect a vehicle's fuel consumption, CO₂ emissions and performance figures.

**Value range taking into account different chassis (steel spring and air spring) and equipment lines in relation to the basic model.