Technical Data	Audi S3 Sedan TFSI
Program for Germany	Status: 08/11/2020
Engine / electrics	
Engine type	Inline 4-cylinder engine
Valve gear / number of valves per cylinder	Roller cam follower, continuous intake and exhaust camshaft adjustment, hydraulic valve-play compensation / 2/2 inlet/exhaust valves per cylinder
Displacement in cc / bore x stroke in mm / compression	1984 / 82.5 x 92.8 / 9.3
Max. power output in kW (PS) / rpm	228 (310) / 5450 - 6500
Max. torque in Nm <i>(lb-ft)</i> / at rpm	400 (295.0) / 2000 - 5450
Mixture preparation	Direct injection, lambda control, knock control, turbocharger, intercooler
Exhaust emission control	Catalytic converter, oxygen sensor, gasoline particulate filter
Emissions standard	EU6
Start-stop / REM	yes / yes
Battery in A / Ah	380 / 68
Max. electrical output at 12V in kilowatts	1.6
On-board voltage 1 in volts	12
Drivetrain / transmission	
Drive type	quattro permanent all-wheel drive with electronically controlled multi-plate clutch
Type of center differential	Electronically controlled multi-plate clutch
Type of rear axle differential	Standard
Clutch	2 electrohydraulically controlled multi-plate clutches in an oil bath
Transmission type	7-speed S tronic
Transmission ratio in 1st/2nd gear	3.190 / 2.750
Transmission ratio in 3rd/4th gear	1.897 / 1.040
Transmission ratio in 5th/6th gear	0.661 / -
Reverse gear ratio / final drive ratio 1-2 / 2-3	2.9 / 4.471 / 3.304
Suspension / steering / brakes	
Type and design of front-axle suspension	McPherson struts, front
Type and design of rear-axle suspension	Four-link rear suspension
Steering	Electromechanical progressive steering with speed-dependent power assistance
Steering ratio	14.3
Turning circle in m (ft)	11.1 (36.4)
Brake control system	Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist
Tires (basic)	225/40 R 18 92 Y XL
Wheels (basic)	Alloy 8 J x 18"
Performance / acoustics	
Top speed in km/h <i>(mph)</i>	250 (155.3)
Limited	yes
Acceleration, 0-100 km/h (0-62.1 mph)	4.8
Fuel type / octane value	Gasoline / 95
Fuel standard	DIN EN 228 (gasoline)
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)	81.7 / 70

Consumption / emissions*	
Fuel consumption, urban / extra-urban / combined	
in liters per 100 kilometers (US mpg)	9,1 (25.8) / 6,2 (37.9) / 7,3 - 7,2 (32.2 - 32.6)
CO ₂ emissions combined in grams per kilometer (g/mi)	166 - 165 (267.2 - 265.5)
Servicing / guarantee (Germany)	
Service interval	30,000 km (18,641.1 mi) / 2 years, whichever comes first
Vehicle / paint / rust perforation guarantee	2/3/12 (years)
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive	13 / 25 / 26
Weights / loads	
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)	1505 (3318.0) / 1580 (3483.3) / 2025 (4464.4)
Front/rear axle load limit in kg (<i>lb</i>)	1095 (2414.1) / 1030 (2270.8)
Roof load limit / permissible nose weight in kg (<i>lb</i>)	75 (165.3) / -
Capacities	
Cooling system capacity (incl. heating) in liters (US gal)	9.6 (2.5)
Engine oil capacity, including filter (change volume) in liters (<i>US qt)</i>	6.6 <i>(</i> 7 <i>.0)</i>
Fuel tank capacity in liters (US gal)	55 (14.5)
Dimensions / body	
Body type / number of doors	Unitary, steel / 4
Number of seats	5
Drag coefficient Cd / frontal area A in m ² (<i>sq ft</i>)	0.29 / 2.17 (23.4)
Standard dimensions (length / width excluding mirrors / height with steel springs) in mm <i>(ft)</i>	4504 (14.8) / 1816 (6.0) / 1415 (4.6) / -
Width including mirrors in mm (ft)	1984 (6.5)
Wheelbase / track width front/rear in mm (ft)	2630 (8.6) / 1545 (5.1) / 1519 (5.0)
Height of loading edge with steel springs in mm (ft)	677 (2.2)
Luggage capacity behind 2nd seat bench, open / closed in l <i>(cu ft)</i>	- / 325 (11.5)

 * Fuel consumption and CO_2 emission figures given in ranges depend on the tires/wheels used