



## Technical data Audi RS 5 DTM (2017)

As of: May 2017

Model	Audi RS 5 DTM (2017)
Vehicle	
Vehicle type	DTM touring car
Chassis	Carbon fiber monocoque with integrated fuel cell,
	front, rear and lateral CFRP crash elements
Engine	
Туре	Normally aspirated petrol 90° V8, 4 valves per cylinder,
	mandatory intake air restrictors – 2 x 29.0 mm
Engine management	Bosch MS 5.1
Engine lubrication	Dry sump
Cubic capacity	4,000 cc
Power	More than 500 hp More than 500 Nm
Torque	More than 500 Nm
Drivetrain/transmission	
Transmission type	Rear wheel drive
Clutch	4-plate carbon clutch
Gearbox	Semi-automatic 6-speed gearbox with paddle shift
Differential	Adjustable plate-type limited-slip differential
Driveshafts	Tripod-joint driveshafts
Suspension/steering/brakes	
Steering	Servo assisted rack and pinion steering
Suspension	Independent front and rear suspension, double wishbones, pushrod
	system with spring/damper unit, adjustable gas pressure dampers
Brakes	Hydraulic dual circuit brake system, light alloy monobloc brake calipers,
	ventilated front and rear carbon fiber brake discs, infinitely manually
Wheels	adjustable front and rear brake balance, electromagnetic start valve  Forged aluminum wheels
Wileels	front: 12 x 18 inch; rear: 13 x 18 inch
Tires	Hankook.
11103	front: 300-680-18; rear: 320-710-18
	110 htt 300 000 10, 100h 320 110 10
Weight/dimensions	
Length	5,010 mm (including rear wing)
Width	1,950 mm
Height	1,150 mm
Minimum weight Fuel tank capacity	1,125 kg (including driver) 120 l
ruer tank capacity	1201